



**CTS (GUANGZHOU) TESTING SERVICE TECHNOLOGY
INTERNATIONAL**

OPERATE ACCORDING TO ISO/IEC 17025

EMC TEST REPORT

TEST REPORT NUMBER : CNB3111117-04890-E



CTS (Guangzhou) Testing Service Technology Co., Ltd.
Building F, Dachuang Industrial Park, No.379, Zhongshan Dadao,
Guangzhou, China



TEST REPORT EN 61000-6-3:2007 Electromagnetic compatibility (EMC) —Part 6-3: Generic standards — Emission standard for residential, commercial and light-industrial environments EN 61000-6-1:2007 Electromagnetic compatibility (EMC) —Part 6-1: Generic standards — Immunity for residential, commercial and light-industrial environments	
Report Reference No.	CNB3111117-04890-E
Date of issue	18 November 2011
Testing Laboratory Name	CTS (Guangzhou) Testing Service Technology Co., Ltd.
Address	Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China.
Testing location/ procedure	Full application of Harmonised standards <input checked="" type="checkbox"/> Partial application of Harmonised standards <input type="checkbox"/> Other standard testing method <input type="checkbox"/>
Applicant's name	
Address	
Test specification:	
Standard	EN 61000-6-3:2007, EN 61000-6-1:2007
Test Report Form No.	CTSEMC-1.0
TRF Originator	CTS (Guangzhou) Testing Service Technology Co., Ltd.
Master TRF	Dated 2009-01
CTS (Guangzhou) Testing Service Technology Co., Ltd. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the CTS (Guangzhou) Testing Service Technology Co., Ltd. is acknowledged as copyright owner and source of the material. CTS (Guangzhou) Testing Service Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test item description	Luggage Scale
Trade Mark	/
Manufacturer	
Model/Type reference	HS-016
Ratings	Battery 3V
Result	Positive

Compiled by:

Violet

Violet Lee / File administrators

Supervised by:

Tom

Tom Xiao / Technique principal

Approved by:



Vincent yao / Manager



Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



EMC -- TEST REPORT

Test Report No. : CNB3111117-04890-E

18 November 2011
Date of issue

Type / Model..... HS-016

EUT..... Luggage Scale

Applicant.....

Address.....

Telephone.....

Fax.....

Contact.....

Manufacturer.....

Address.....

Telephone.....

Fax.....

Contact.....

Factory.....

Address.....

Telephone.....

Fax.....

Contact.....

Test Result according to the standards on page 3: **Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

TABLE OF CONTENTS

Description	Page
1 TEST STANDARDS	4
2 SUMMARY	4
2.1 GENERAL REMARKS	4
2.2 FINAL ASSESSMENT	4
3 EQUIPMENT UNDER TEST	5
3.1 Power supply system utilised	5
3.2 Short description of the Equipment under Test (EUT).....	5
3.3 EUT operation mode	5
3.4 EUT configuration.....	6
3.5 Performance level.....	6
3.6 Definition related to the performance level	6
4 TEST ENVIRONMENT	7
4.1 Address of the test laboratory	7
4.2 Test facility	7
4.3 Environmental conditions.....	7
4.4 Definitions of symbols used in this test report.....	7
4.5 Statement of the measurement uncertainty	7
4.6 Measurement Uncertainty	8
4.7 Test Description	8
5 TEST CONDITIONS AND RESULTS	9
5.1 Radiated disturbance (electric field)	9
5.2 Electrostatic discharge	15
5.3 Radiated, radio-frequency, electromagnetic field	17
5.4 Power frequency magnetic field	19
6 USED TEST EQUIPMENT.....	21
7 TEST PHOTOGRAPHS.....	24
7.1. Photos of radiated emission measurement	24
7.2. Photo of electrostatic discharge Immunity measurement.....	24
7.3. Photo of RF field strength Immunity measurement	24
7.4. Photo of PFM field immunity measurement	25
8 EXTERNAL AND INTERNAL PHOTOS OF THE EUT.....	26
9 Manufacturer/ Approval holder Declaration.....	28

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

1 TEST STANDARDS

The tests were performed according to following standards:

EN 61000-6-3:2007 Electromagnetic compatibility (EMC) —Part 6-3: Generic standards — Emission standard for residential, commercial and light-industrial environments

EN 61000-6-1:2007 Electromagnetic compatibility (EMC) —Part 6-1: Generic standards — Immunity for residential, commercial and light-industrial environments

2 SUMMARY

2.1 GENERAL REMARKS

Date of receipt of test sample	17 November 2011
Testing commenced on	18 November 2011
Testing concluded on	18 November 2011

2.2 FINAL ASSESSMENT

The EMC requirements pertaining to the technical standards and tested operation modes are

☒ - fulfilled.

☐ - **not** fulfilled.

The equipment under test

☒ - fulfils the EMC requirements cited on page 3.

☐ - **does not** fulfil the EMC requirements cited on page 3.

3 EQUIPMENT UNDER TEST

3.1 Power supply system utilised

Power supply voltage: ☐ AC 230V/50 Hz ☐ 115V/60Hz
☒ Battery 3V ☐ 24 V DC
☐ Other (Specified blank below)

3.2 Short description of the Equipment under Test (EUT)

Number of tested samples: 1
Serial number: Prototype

3.3 EUT operation mode

The equipment under test was operated during the measurement under the following conditions:

- ☐ - Standby
- ☐ - Test programme (H - Pattern)
- ☐ - Test programme (colour bar)
- ☐ - Operating mode 2500 U/min. (1 cylinder)
- ☐ - Operating mode 1500 U/min. (> 1 cylinder)
- ☐ - Ignition on , Motor off
- ☐ - Speed 50 km/h
- ☒ - Test program (customer specific)

Operating Mode: ON

Emissions tests.....: According to EN 61000-6-3, searching for the highest disturbance.

Immunity tests : According to EN 61000-6-1, searching for the highest susceptibility.

3.4 EUT configuration

(The CDF filled by the applicant can be viewed at the test laboratory.)

The following peripheral devices and interface cables were connected during the measurement:

Not Applicable

3.5 Performance level

The test results shall be classified in terms of the loss of function or degradation of performance of the equipment under test, relative to a performance level defined by its manufacturer or the requestor of the test, or agreed between the manufacturer and the purchaser of the product.

3.6 Definition related to the performance level

- ☒ based on the used product standard
- ☐ based on the declaration of the manufacturer, requestor or purchaser

Criterion A:

Definition: normal performance within limits specified by the manufacturer, requestor or purchaser:

Criterion B:

Definition: temporary loss of function or degradation of performance which ceases after the disturbance ceases, and from which the equipment under test recovers its normal performance, without operator intervention:

Criterion C:

Definition: temporary loss of function or degradation of performance, the correction of which requires operator intervention:

Criterion D:

Definition: loss of function or degradation of performance, which is not recoverable, owing to damage to hardware or software, or loss of data:

4 TEST ENVIRONMENT

4.1 Address of the test laboratory

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

4.2 Test facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L3394

CTS (Guangzhou) Testing Service Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01: 2006 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

IC-Registration No.: 8374A

The 3m Alternate Test Site of CTS (Guangzhou) Testing Service Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 8374A on June 06, 2011 .

FCC-Registration No.: 971995

CTS (Guangzhou) Testing Service Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration No.971995, July 21, 2009.

4.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35 ° C
Humidity:	25~75 %
Atmospheric pressure:	86~106 kPa

4.4 Definitions of symbols used in this test report

- - The black square indicates that the listed condition, standard or equipment is applicable for this report.
- - The empty square indicates that the listed condition, standard or equipment is **not** applicable for this report.

4.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the CTS quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

4.6 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Conduction disturbance	150kHz~30MHz	$\pm 1.22\text{dB}$	(1)
Power disturbance	30MHz~300MHz	$\pm 1.38\text{dB}$	(1)
Radiation emission (3m)	30MHz~300MHz	$\pm 3.14\text{dB}$	(1)
	300MHz~1000MHz	$\pm 3.18\text{dB}$	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.
- (2) The actual EUT tested items in this test report, only applies to this "measurement uncertainty" in part / all of the corresponding data.

4.7 Test Description

4.7.1 Description of Standards and Results

EMISSION (EN 61000-6-3:2007)			
Description of Test Item	Standard	Limits	Results
Conducted disturbance at mains terminals	EN 61000-6-3:2007	Class B	N/A
Conducted disturbance at telecommunication port	EN 61000-6-3:2007	Class B	N/A
Radiated disturbance	EN 61000-6-3:2007	Class B	PASS
Harmonic current emissions	EN 61000-3-2:2006+A1:2008+A2:2009	Class A	N/A
Voltage fluctuations & flicker	EN 61000-3-3:2008	-----	N/A
IMMUNITY (EN 61000-6-1:2007)			
Description of Test Item	Basic Standard	Performance Criteria	Results
Electrostatic discharge (ESD)	IEC 61000-4-2:2008	B	PASS
Radio-frequency, Continuous radiated disturbance	IEC 61000-4-3:2010	A	PASS
Electrical fast transient (EFT)	IEC 61000-4-4:2007	B	N/A
Surge (Input a.c. power ports)	IEC 61000-4-5:2009	B	N/A
Radio-frequency, Continuous conducted disturbance	IEC 61000-4-6:2008	A	N/A
Power frequency magnetic field	IEC 61000-4-8:2009	A	PASS
Voltage dips, >95% reduction	IEC 61000-4-11:2010	B	N/A
Voltage dips, 30% reduction		B	N/A
Voltage interruptions		C	N/A
N/A is an abbreviation for Not Applicable.			

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

5 TEST CONDITIONS AND RESULTS

5.1 Radiated disturbance (electric field)

For test instruments and accessories used see section 6 part 6.1.

5.1.1 Description of the test location

Test location : Semi-Anechoic chamber


Test disturbance: 3 Meter

5.1.2 Description of the test set-up

5.1.2.1 Operating Condition

The EUT is engraving during the test, and the results of the maximum emanation are recorded

5.1.2.2 Block Diagram of Test Setup



5.1.3 Limits of disturbance (Class B)

Frequency (MHz)	Distance (Meters)	Field Strengths Limits (dBμV/m)
30 ~ 230	3	40
230 ~ 1000	3	47

Note: (1) The tighter limit shall apply at the edge between two frequency bands.
 (2) Distance refers to the distance in meters between the test instrument antenna and the closest point of any part of the E.U.T.

5.1.4 Test result

The requirements are	Fulfilled
Band width	120kHz
Frequency range	30 MHz - 1000 MHz
Min. limit margin	>4.76 dB at 30 - 1000 MHz

Remarks: The limits are kept. For detailed results, please see the following page(s).

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406


Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

5.1.5 Test protocol

Test point: Operation mode Remarks:	Horizontal	Result:	<input checked="" type="checkbox"/> - passed <input type="checkbox"/> - not passed
EUT	Luggage Scale		
Operating Condition	Battery 3V		
Test Condition	Ambient Temperature: 24°C Humidity: 56%		
Operator	Cherry		
MODEL NO.	HS-016		



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	95.3307	5.01	29.42	34.43	40.00	-5.57	QP
2	132.6052	6.55	27.07	33.62	40.00	-6.38	QP
3	156.6533	6.55	27.19	33.74	40.00	-6.26	QP
4	174.2886	7.42	27.82	35.24	40.00	-4.76	QP
5	189.1182	7.40	27.18	34.58	40.00	-5.42	QP
6	209.5591	7.30	27.90	35.20	40.00	-4.80	QP

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China


Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	609.5992	9.47	29.30	38.77	47.00	-8.23	QP
2	651.2625	9.77	28.76	38.53	47.00	-8.47	QP
3	725.3307	10.25	29.06	39.31	47.00	-7.69	QP
4	794.7695	10.05	30.20	40.25	47.00	-6.75	QP
5	896.6132	10.50	28.79	39.29	47.00	-7.71	QP
6	970.6814	10.50	29.20	39.70	47.00	-7.30	QP

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406


Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Test point:	Vertical	Result:	<input checked="" type="checkbox"/> - passed
Operation mode			<input type="checkbox"/> - not passed
Remarks:			

EUT	Luggage Scale
MODEL NO.	HS-016
Operating Condition	Battery 3V
Test Condition	Ambient Temperature: 24°C Humidity: 56%
Operator	Cherry



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	121.7836	6.52	27.71	34.23	40.00	-5.77	QP
2	125.3908	6.55	26.93	33.48	40.00	-6.52	QP
3	144.2285	6.38	27.34	33.72	40.00	-6.28	QP
4	174.2886	7.42	27.13	34.55	40.00	-5.45	QP
5	211.9639	7.43	26.97	34.40	40.00	-5.60	QP
6	224.7896	7.97	26.96	34.93	40.00	-5.07	QP

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China


Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	638.9178	9.75	29.19	38.94	47.00	-8.06	QP
2	694.4689	10.31	29.31	39.62	47.00	-7.38	QP
3	739.2184	10.25	30.02	40.27	47.00	-6.73	QP
4	853.4068	10.28	28.92	39.20	47.00	-7.80	QP
5	901.2425	10.50	29.48	39.98	47.00	-7.02	QP
6	955.2505	10.50	29.65	40.15	47.00	-6.85	QP

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

5.2 Electrostatic discharge

For test instruments and accessories used see section 6 part 6.6.

5.2.1 Description of the test location

Test location :	Test location no. 2
Power supply:	Battery 3V
Test condition:	Ambient Temperature: 24°C, Humidity:56%
Date of test :	18 November 2011
Operator :	Cherry

5.2.2 Severity of levels electrostatic discharge

5.2.2.1 Severity level: Contact discharge at $\pm 4\text{KV}$ air discharge at $\pm 8\text{KV}$

Level	Test Voltage Contact Discharge (kV)	Test Voltage Air Discharge (kV)
1	2	2
2	4	4
3	6	8
4	8	15
X	Special	Special


5.2.2.2 Performance criterion: B

5.2.3 Description of the test set-up

5.2.3.1 Operating Condition

The EUT is engraving during the test, and the results of the maximum emanation are recorded

5.2.3.2 Block Diagram of Test Setup



IEC 063/98

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

5.2.4 Test specification:

Contact discharge voltage:	<input checked="" type="checkbox"/> 2 kV	<input checked="" type="checkbox"/> 4 kV
Air discharge voltage:	<input checked="" type="checkbox"/> 2 kV	<input checked="" type="checkbox"/> 4 kV <input checked="" type="checkbox"/> 8 kV
Discharge impedance:	<input checked="" type="checkbox"/> 330 Ω / 150 pF	
Discharge factor:	<input checked="" type="checkbox"/> ≥ 1 sec.	
Number of discharges:	<input checked="" type="checkbox"/> ≥ 10	
Type of discharge:	Direct discharge	<input checked="" type="checkbox"/> Air discharge
		<input checked="" type="checkbox"/> Contact discharge
	Indirect discharge	<input checked="" type="checkbox"/> Contact discharge
Polarity:	<input checked="" type="checkbox"/> Positive	<input checked="" type="checkbox"/> Negative
Discharge location:	<input checked="" type="checkbox"/> see photo documentation of the test set-up	
	<input checked="" type="checkbox"/> all external locations accessible by hand	
	<input checked="" type="checkbox"/> horizontal plate (HCP)	
	<input checked="" type="checkbox"/> vertical coupling plate (VCP)	

5.2.5 Test result

The requirements are **Fulfilled**

Performance Criterion: **B**

Remarks: During the test no deviation was detected to the selected operation mode(s).

5.3 Radiated, radio-frequency, electromagnetic field

For test instruments and accessories used see section 6 part 6.7.

5.3.1 Description of the test location

Test location :	Test location no. 2
Power supply:	Battery 3V
Test condition:	Ambient Temperature: 24°C, Humidity:56%
Date of test :	18 November 2011
Operator :	Cherry

5.3.2 Severity levels of radiated, Radio-frequency, electromagnetic field

5.3.2.1 Severity level: 3V/m

Level	Field strenght(V/m)
1	1
2	3
3	10
X	Special


5.3.2.2 Performance criterion: A

5.3.3 Description of the test set-up

5.3.3.1 Operating Condition

The EUT is engraving during the test, and the results of the maximum emanation are recorded

5.3.3.2 Block Diagram of Test Setup



IEC 034/06

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

5.3.4 Test specification:

Frequency range:	■ 80 MHz to 1000 MHz
Field strength:	■ 3 V/m
EUT - antenna separation:	■ 3 m
Modulation:	■ AM: 80 % ■ sinusoidal 1000Hz
Frequency step:	■ 1 % with 3 s dwell time
Antenna polarisation:	■ horizontal ■ vertical

5.3.5 Test resultThe requirements are **Fulfilled**Performance Criterion: **A****Remarks:** During the test no deviation was detected to the selected operation mode(s).

5.4 Power frequency magnetic field

For test instruments and accessories used see section 6 part 6.11.

5.4.1 Description of the test location

Test location :	Test location no. 2
Power supply:	Battery 3V
Test condition:	Ambient Temperature: 24°C, Humidity:56%
Date of test :	18 November 2011
Operator :	Cherry

5.4.2 Severity levels of magnetic field immunity

5.4.2.1 Severity Level: 3A/m

Level	Magnetic Field Strength (A/m)
1	1
2	3
3	10
4	30
5	100
X	Special


5.4.2.2 Performance Criterion: A

5.4.3 Description of the test set-up

5.4.3.1 Operating Condition

The EUT is engraving during the test, and the results of the maximum emanation are recorded

5.4.3.2 Block Diagram of Test Setup



Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

5.4.4 Test specification:

Test frequency:	<input checked="" type="checkbox"/> 50 Hz		
Continuous field:	<input checked="" type="checkbox"/> 3 A/m		
Duration (Continuous field):	<input checked="" type="checkbox"/> 60 s each Axis		
Short duration (1-3s):	<input checked="" type="checkbox"/> 300 A/m		
Axis:	<input checked="" type="checkbox"/> x-axis	<input checked="" type="checkbox"/> y-axis	<input checked="" type="checkbox"/> z-axis

5.4.5 Test resultThe requirements are **Fulfilled**Performance Criterion: **A****Remarks:** During the test no deviation was detected to the selected operation mode(s).

6 USED TEST EQUIPMENT

6.1

Radiated Emission(Electric field)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	100868	2010/12
2	Biconical Antenna	ROHDE & SCHWARZ	HK116	100221	2010/12
3	Log per Antenna	ROHDE & SCHWARZ	HL223	100226	2010/12
4	Log per Antenna	ROHDE & SCHWARZ	HL050	100186	2010/12
5	EMI Test Software	ROHDE & SCHWARZ	ESK1	N/A	2010/12

6.2

Power Disturbance					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	ROHDE &SCHWARZ	ESVS10	842885/001	2010/12
2	Absorbing clamp	ROHDE &SCHWARZ	MDS 21	03466	2010/12
3	EMI Test Software	ROHDE &SCHWARZ	ESK1	N/A	2010/12

6.1

Conducted Disturbance					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	ROHDE & SCHWARZ	ESHS10	842884/012	2010/12
2	Artificial Mains	ROHDE & SCHWARZ	ESH3-Z5	832479/025	2010/12
3	Pulse Limiter	ROHDE & SCHWARZ	ESHSZ2	100301	2010/12
4	EMI Test Software	ROHDE & SCHWARZ	ESK1	N/A	2010/12

6.4

Harmonic Current					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	Harmonic And Flicker Analyzer	EMC Partner	HAR1H01B	HAR1000-48	2010/12

6.5

Voltage fluctuation and Flicker					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	Harmonic And Flicker Analyzer	EMC Partner	HAR1H01B	HAR1000-48	2010/12

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

6.6

Electrostatic Discharge					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	ESD Simulator	Schlöder	SESD 200	302016	2010/12

6.7

RF Field Strength Susceptibility					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	SIGNAL GENERATOR	ROHDE & SCHWARZ	SMY 01	843215/014	2010/12
2	AMPLIFIER	KALMUS	713FC	Jan-85	2010/12
3	EMS Test Software	ROHDE & SCHWARZ	ESK1	N/A	2010/12

6.8

Electrical Fast Transient/Burst					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMC test system Transient-1000	EMC Partner	TRA1H01B	HAR1000-78	2010/12
2	Coupling Clamp	EMC Partner	SFT 410	302015	2010/12

6.9

Surge					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMC test system Transient-1000	EMC Partner	TRA1H01B	HAR1000-78	2010/12

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

6.10

Conducted Susceptibility					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	RF generator / amplifier	Schlöder	CDG 6000	HU906007	2010/12
2	CDN	Schlöder	CDN M3	A3003008	2010/12
3	CDN	Schlöder	CDN T2	A3010005	2010/12
4	EM injection clamp	Liithi	EM101	35670	2010/12
5	EMS Test Software	ROHDE & SCHWARZ	ESK1	N/A	2010/12

6.11

Power Frequency Magnetic Field Susceptibility					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	Power frequency mag-field generator System	EM TEST	EMS61000-8K	409001	2010/12

6.12

Voltage Dips					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMC test system Transient-1000	EMC Partner	TRA1H01B	HAR1000-78	2010/12

6.13

Voltage Short Interruptions					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMC test system Transient-1000	EMC Partner	TRA1H01B	HAR1000-78	2010/12

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn


See Reverse For Terms And Conditions of Service

7 TEST PHOTOGRAPHS

7.1. Photos of radiated emission measurement



7.2. Photo of electrostatic discharge Immunity measurement



7.3. Photo of RF field strength Immunity measurement



Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.
Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China
Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406
Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

7.4. Photo of PFM field immunity measurement



Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

8 EXTERNAL AND INTERNAL PHOTOS OF THE EUT



External view front



External view base



External view side

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China


Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

**Internal view****PCB layout****PCB solder**

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

9 Manufacturer/ Approval holder Declaration

The following identical model(s):

N/A

Belong to the tested device:

Product description: **Luggage Scale**
Model name: **HS-016**

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CTS (Guangzhou) Testing Service Technology Co., Ltd.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service