



EMC TEST REPORT

For

China Etech Groups Ltd

Car charger

Model No. : ECC014

Prepared By : Shenzhen Certification Technology Service Co., Ltd.

**Address : 2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China**

Tel: 400-6786199

Fax: (0755) 26736857

Report Number	: CSTE141215006
Date of Receipt	: December 15, 2014
Date of Test	: December 15-17, 2014
Date of Report	: December 19, 2014
Version Number	: REV0

TABLE OF CONTENTS

Description	Page
Test Report Declaration.....	5
1. SUMMARY OF STANDARDS AND RESULTS	6
1.1. Description of Standards and Results	6
2. GENERAL INFORMATION	7
2.1. Description of Device (EUT).....	7
2.2. Tested Supporting System Details.....	7
2.3. Block Diagram of connection between EUT and simulators.....	8
2.4. Test Facility	9
2.5. Measurement Uncertainty	9
2.6. Test mode Description	10
3. CONDUCTED Disturbance at Mains Terminals Test	11
3.1. Test Equipment	11
3.2. Block Diagram of Test Setup.....	11
3.3. Test Standard	11
3.4. Power Line Conducted Disturbance at Mains Terminals Limit	11
3.5. EUT Configuration on Test	12
3.6. Operating Condition of EUT	12
3.7. Test Procedure	12
3.8. Conducted Disturbance at Mains Terminals Test Results	12
4. Radiated Disturbance test	13
4.1. Test Equipments	13
4.2. Block Diagram of Test Setup.....	13
4.3. Test Standard	14
4.4. Radiated Disturbance Limit	14
4.5. EUT Configuration on Test	14
4.6. Operating Condition of EUT	15
4.7. Test Procedure	15
4.8. Radiated Disturbance Test Results	16
5. harmonic CURRENT TEST	19
5.1. Test Equipments	19
5.2. Block Diagram of Test Setup.....	19
5.3. Test Standard	19
5.4. Limits of Harmonic Current	19
5.5. Operating Condition of EUT	20
5.6. Test Procedure	20
5.7. Test Results.....	20
6. VOLTAGE FLUCTUATIONS & FLICKER TEST	21
6.1. Test Equipment	21
6.2. Block Diagram of Test Setup.....	21
6.3. Test Standard	21
6.4. Limits of Voltage Fluctuation and Flick	21
6.5. Operating Condition of EUT	21
6.6. Test Procedure	21
6.7. Test Results.....	21
7. IMMUNITY PERFORMANCE CRITERIA	22
8. Electrostatic Discharge immunity Test	23
8.1. Test Equipments	23



8.2.	Block Diagram of Test Setup.....	23
8.3.	Test Standard	23
8.4.	Severity Levels and Performance Criterion.....	23
8.5.	EUT Configuration	23
8.6.	Operating Condition of EUT	23
8.7.	Test Procedure	24
8.8.	Test Results.....	24
9.	RF Field Strength susceptibility Test.....	26
9.1.	Test Equipments	26
9.2.	Block Diagram of Test Setup.....	26
9.3.	Test Standard	26
9.4.	Severity Levels and Performance Criterion.....	27
9.5.	EUT Configuration	27
9.6.	Operating Condition of EUT	27
9.7.	Test Procedure	27
9.8.	Test Results.....	27
10.	Electrical Fast Transient/Burst immuNity Test.....	29
10.1.	Test Equipments	29
10.2.	Block Diagram of Test Setup.....	29
10.3.	Test Standard	29
10.4.	Severity Levels and Performance Criterion.....	29
10.5.	EUT Configuration	29
10.6.	Operating Condition of EUT	29
10.7.	Test Procedure	30
10.8.	Test Results.....	30
11.	SURGE Test.....	31
11.1.	Test Equipments	31
11.2.	Block Diagram of Test Setup.....	31
11.3.	Test Standard	31
11.4.	Severity Levels and Performance Criterion.....	31
11.5.	EUT Configuration	31
11.6.	Operating Condition of EUT	31
11.7.	Test Procedure	32
11.8.	Test Results.....	32
12.	Injected currents susceptibility test.....	33
12.1.	Test Equipments	33
12.2.	Block Diagram of Test Setup.....	33
12.3.	Test Standard	33
12.4.	Severity Levels and Performance Criterion.....	33
12.5.	EUT Configuration	34
12.6.	Operating Condition of EUT	34
12.7.	Test Procedure	34
12.8.	Test Results.....	34
13.	magnetic field immunity test.....	35
13.1.	Test Equipments	35
13.2.	Block Diagram of Test Setup.....	35
13.3.	Test Standard	35
13.4.	Severity Levels and Performance Criterion.....	35
13.5.	EUT Configuration on Test	36
13.6.	Operating Condition of EUT	36



13.7.	Test Procedure	36
13.8.	Test Results	36
14.	Voltage dips and interruptions test	37
14.1.	Test Equipment	37
14.2.	Block Diagram of Test Setup	37
14.3.	Test Standard	37
14.4.	Severity Levels and Performance Criterion	37
14.5.	EUT Configuration	37
14.6.	Operating Condition of EUT	37
14.7.	Test Procedure	38
14.8.	Test Results	38
15.	Photographs	39
15.1.	Photos of Radiated Emission Test (In Anechoic Chamber)	39
15.2.	Photos of Electrostatic Discharge Immunity Test	39
16.	photos of the EUT	40



TEST REPORT VERIFICATION

Applicant

Manufacturer

EUT Description : Car charger

(A) Model No. : ECC014

(B) Trademark : N/A

(C) Ratings Supply : DC 12V

(D) Test Voltage : DC 12V From Battery

Measurement Standard Used:

EN 55022:2010 (Class B)

EN 55024:2010

(IEC 61000-4-2:2008; IEC 61000-4-3:2006+A1:2007+A2:2010)

The device described above is tested by Shenzhen Certification Technology Service Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen Certification Technology Service Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. Also, this report shows that the EUT is technically compliant with the EN 55022, EN 61000-3-2, EN 61000-3-3 and EN 55024 requirements.

This report applies to above tested sample only.

Tested by (name + signature).....

Reak Yang
Test Engineer

Reak Yang

Approved by (name + signature).....

Simple Guan
Project Manager

Simple Guan



Date of issue.....

December 19, 2014

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION				
Description of Test Item	Standard	Limits		Results
Conducted disturbance at mains terminals	EN 55022: 2010	Class B		N/A
Conducted disturbance at telecommunication port	EN 55022: 2010	Class B		N/A
Radiated disturbance	EN 55022: 2010	Class B		PASS
Harmonic current emissions	EN61000-3-2:2006+ A1:2009+A2:2009	Class A		N/A
Voltage fluctuations & flicker	EN 61000-3-3:2013	Section 5		N/A
IMMUNITY (EN 55024: 2010)				
Description of Test Item	Basic Standard	Performance Criteria	Observation Criteria	Results
Electrostatic discharge (ESD)	IEC 61000-4-2:2008	B	B	PASS
Radio-frequency, Continuous radiated disturbance	IEC 61000-4-3:2006+ A1:2007+A2:2010	A	A	PASS
Electrical fast transient (EFT)	IEC 61000-4-4:2012	B	N/A	N/A
Surge (Input a.c. power port)	IEC 61000-4-5:2005	B	N/A	N/A
Surge(Telecommunication port)		B	N/A	N/A
Radio-frequency, Continuous conducted disturbance	IEC 61000-4-6:2008	A	N/A	N/A
Power frequency magnetic field	IEC 61000-4-8:2009	A	N/A	N/A
Voltage dips, >95% reduction	IEC 61000-4-11:2004	B	N/A	N/A
Voltage dips, 30% reduction		C	N/A	N/A
Voltage interruptions		C	N/A	N/A
N/A is an abbreviation for Not Applicable.				

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

Description	:	Car charger
Classification	:	Class III
Model Number	:	ECC014
EUT	:	Input: DC 12V Output: DC 5V, 1000mA
Trademark	:	N/A
Applicant	:	China Etech Groups Ltd
Address	:	Room 3A15, Floor 4, Block C, Bao Yuan Huafeng Headquarter, economy building, Xixiang Road, Xixiang street, Bao an District, Shenzhen, China
Manufacturer	:	China Etech Groups Ltd
Address	:	Room 3A15, Floor 4, Block C, Bao Yuan Huafeng Headquarter, economy building, Xixiang Road, Xixiang street, Bao an District, Shenzhen, China
Sample Type	:	Prototype production

2.2. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number
1.	Battery (12V)	N/A	N/A	N/A
2.	Load	N/A	N/A	N/A

Signal Cable Description of the above Support Units					
No.	Port Name	Cable	Length	Shielded (Yes or No)	Detachable (Yes or No)
1.	N/A	N/A	N/A	N/A	N/A

2.3. Block Diagram of connection between EUT and simulators

For EMI Tests



For EMS Tests



※ EUT: Car charger

2.4. Test Facility

2.4.1. Laboratory Name:

Shenzhen Certification Technology Service Co., Ltd.

2.4.2. Site Location :

2F, Building B, East Area of Nanchang Second Industrial Zone,
Gushu 2nd Road, Bao'an District, Shenzhen 518126, P.R. China

2.4.3. Test facility:

JAN 13, 2012 File on Federal Communication Commission
Registration Number:197647

October 11, 2011 Certificated by IC
Registration Number: 8528B

2.5. Measurement Uncertainty

(95% confidence levels, k=2)

Test Item	Uncertainty	U _{cispr}
Uncertainty for Conduction emission test	2.50dB	3.8 dB
Uncertainty for Radiation Emission test	3.04 dB (Distance: 3m Polarize: V)	5.2 dB
	3.02 dB (Distance: 3m Polarize: H)	
Uncertainty for Radiation Emission test (1GHz-18GHz)	3.56 dB (Distance: 3m Polarize: V)	5.2 dB
	3.84 dB (Distance: 3m Polarize: H)	
Uncertainty for Flicker test	0.05%	N/A
Uncertainty for Harmonic test	1.8%	N/A

2.6. Test mode Description


No.	Test Mode
※1.	Full Load
2.	Half Load
3.	No Load
Note: ※ is worst case mode, so this report only reflected the worst mode	

3. CONDUCTED DISTURBANCE AT MAINS TERMINALS TEST

3.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI	100843	Jan 20, 14	1 Year
2.	L.I.S.N.#1	Schwarzbeck	NSLK8126	8126466	Jan 20, 14	1 Year
3.	L.I.S.N.#2	Kyoritsu	KNW-242C	8-1920-1	Jan 20, 14	1 Year
4.	Terminator	Hubersuhner	50Ω	No. 1	Jan 20, 14	1 Year
5.	RF Cable	Schwarzbeck	9111505/200	5995-12-161-6890#	Jan 20, 14	1 Year
6.	Coaxial Switch	Schwarzbeck	CX-210	N/A	Jan 20, 14	1 Year
7.	Pulse Limiter	Schwarzbeck	VTSD9516F	9618	Jan 20, 14	1 Year

3.2. Block Diagram of Test Setup



3.3. Test Standard

EN 55022: 2010, Class B

3.4. Power Line Conducted Disturbance at Mains Terminals Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. Emission level=Read level+LISN factor-Preamp factor+Cable loss

2 * Decreasing linearly with logarithm of frequency.

3. The lower limit shall apply at the transition frequencies.

3.5. EUT Configuration on Test

The following equipments are installed on Conducted Emission Test to meet EN 55022 requirement and operating in a manner which tends to maximize its emission characteristics in a normal application.

3.5.1. Support Equipment : As Tested Supporting System Detail, in Section 2.2.

3.6. Operating Condition of EUT

3.6.1. Setup the EUT and simulator as shown as Section 3.2.

3.6.2. Turn on the power of all equipment.

3.6.3. Let Car charger (EUT) work in test mode (Full Load) and measure it.

3.7. Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). This provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N.#2). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to EN 55022 Class B on conducted Disturbance test.

The bandwidth of test receiver (R & S ESHS20) is set at 10kHz.

The frequency range from 150kHz to 30MHz is checked. The test results are reported and test results for Conducted Disturbance Test on Section 3.8.

3.8. Conducted Disturbance at Mains Terminals Test Results

EUT power supplies by DC Power, so this item test not applicable.

4. RADIATED DISTURBANCE TEST

4.1. Test Equipments

4.1.1. For frequency range 30MHz~1000MHz (At Semi Anechoic Chamber)


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Test Receiver	Rohde&Schwarz	ESCI	101165	Jan 20, 14	1 Year
2	Amplifier	Schwarzbeck	BBV9743	9743-019	Jan 20, 14	1 Year
3	Bilog Antenna	Schwarzbeck	VULB 9168	9168-438	Jan 22, 14	2 Year
4	RF Cable	Schwarzbeck	AK9515E	95891-2m	Jan 20, 14	1 Year
5	RF Cable	Schwarzbeck	AK9515E	95891-11m	Jan 20, 14	1 Year
6	RF Cable	Schwarzbeck	AK9515E	95891-0.5m	Jan 20, 14	1 Year

4.1.2. For frequency range 1GHz~6GHz (At Semi Anechoic Chamber)


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	E4407B	MY49510055	Jan 20, 14	1 Year
2	Horn Antenna	Schwarzbeck	BBHA 9120 D	BBHA 9120 D(1201)	Jan 22, 14	2 Year
3	Amplifier	Quietek	AP-180C	CHM-0602012	Jan 20, 14	1 Year
4	RF Cable	Resenberger	Cable 4	N/A	Jan 20, 14	1 Year
5	RF Cable	Resenberger	Cable 5	N/A	Jan 20, 14	1 Year
6	RF Cable	Resenberger	Cable 6	N/A	Jan 20, 14	1 Year

4.2. Block Diagram of Test Setup

4.2.1. In Semi Anechoic Chamber (3m) Test Setup Diagram for 30MHz~1000MHz



4.2.2. In Semi Anechoic Chamber (3m) Test Setup Diagram for 1-6GHz



4.3. Test Standard

EN 55022: 2010, Class B

4.4. Radiated Disturbance Limit

All emanations from a Class B computing devices or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified below:

FREQUENCY (MHz)	DISTANCE (Meters)	FIELD STRENGTHS LIMITS (dB μ V/m)
30 ~ 230	3	40
230 ~ 1000	3	47
1000~3000	3	70(Peak) 50(Average)
3000~6000	3	74(Peak) 54(Average)

Note:

- (1) Emission level = Read level+Antenna Factor-Preamplifier Factor +Cable Loss
- (2) The lower limit shall apply at the transition frequencies.
- (3) Distance refers to the distance in meters between the test instrument antenna and the closed point of any part of the E.U.T.

4.5. EUT Configuration on Test

The EN 55022 Class B regulations test method must be used to find the maximum emission during Radiated Disturbance test. The configuration of EUT is same as used in Conducted Disturbance test. Please refer to Section 3.5.

4.6. Operating Condition of EUT

- 4.6.1. Setup the EUT and simulator as shown as Section 4.2.
- 4.6.2. Turn on the power of all equipment.
- 4.6.3. Let Car charger (EUT) work in test mode (Full Load) and measure it.

4.7. Test Procedure

The EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber. An antenna was located 3m & 3m from the EUT on an adjustable mast. A pre-scan was first performed in order to find prominent radiated emissions. For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all the interface cables were changed according to EN 55022 Class B on Radiated Disturbance test.

The bandwidth setting on the test receiver (ROHDE&SCHWARZ TEST RECEIVER ESCI) is 120 kHz.

The resolution bandwidth of the Agilent Spectrum Analyzer E4407B was set at 1MHz. (For above 1GHz)

The frequency range from 30MHz to 1000MHz was pre-scanned with a peak detector and all final readings of measurement from Test Receiver are Quasi-Peak values.

The frequency range from 1GHz to 6GHz was checked with peak and average detector, measurement distance is 3m in 3m chamber.

Finally, selected operating situations at Semi Anechoic Chamber measurement, all the test results are listed in section 4.8.

4.8. Radiated Disturbance Test Results

PASS. (All emissions not reported below are too low against the prescribed limits.)

The EUT with the following test mode was tested and read QP values, the test results are listed in next pages.


Temperature: 24.2℃ Humidity: 54%

The details of test mode is as follows :

No.	Test Mode
1.	Full Load

For frequency range 1GHz~6GHz


The highest frequency of the internal sources of the EUT is less than 108 MHz, the measurement shall only be made up to 1 GHz. So the frequency rang 1GHz-6GHz radiation test not applicable.



Condition : EN 55022 CLASS B 3m POL: HORIZONTAL
 EUT : Car charger
 Model No : ECC014
 Test Mode : Full Load
 Power : DC 12V
 Test Engineer : Reak
 Remark :
 Temp : 24.2℃
 Hum : 54%

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	33.09	46.85	13.33	31.02	0.11	29.27	40.00	-10.73	QP
2	44.28	45.23	13.79	31.19	0.03	27.86	40.00	-12.14	QP
3	60.28	43.55	12.75	31.31	0.24	25.23	40.00	-14.77	QP
4	102.72	54.80	10.54	31.52	0.28	34.10	40.00	-5.90	QP
5	183.84	55.38	11.20	31.14	0.56	36.00	40.00	-4.00	QP
6	208.58	49.72	10.04	31.58	0.57	28.75	40.00	-11.25	QP

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss



Condition : EN 55022 CLASS B 3m POL: VERTICAL
 EUT : Car charger
 Model No : ECC014
 Test Mode : Full Load
 Power : DC 12V
 Test Engineer : Reak
 Remark :
 Temp : 24.2°C
 Hum : 54%

Item	Freq MHz	Read Level dBuV	Antenna Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	32.07	46.42	13.28	30.98	0.11	28.83	40.00	-11.17	QP
2	58.61	41.51	12.75	31.30	0.23	23.19	40.00	-16.81	QP
3	100.23	52.75	10.35	31.54	0.46	32.02	40.00	-7.98	QP
4	182.56	50.37	11.44	31.12	0.56	31.25	40.00	-8.75	QP
5	207.85	45.38	10.04	31.58	0.49	24.33	40.00	-15.67	QP
6	232.53	41.02	11.26	31.02	0.56	21.82	47.00	-25.18	QP


Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss

5. HARMONIC CURRENT TEST

5.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Harmonics Flicker Analyser	Voltech	PM6000	200006700495	Jan 20, 14	1 Year

5.2. Block Diagram of Test Setup



5.3. Test Standard

EN 61000-3-2: 2006+A1:2009+A2:2009; Class A

5.4. Limits of Harmonic Current

Limits for Class D Equipment		
Harmonic order (n)	Maximum permissible harmonic current per watt (mA/W)	Maximum permissible harmonic current (A)
3	3.4	0.23
5	1.9	1.14
7	1.0	0.77
9	0.5	0.40
11	0.35	0.33
13	0.30	0.21
15≤n≤39 (odd harmonic only)	3.85/n	0.15×15/n

Limits for Class A equipment	
Harmonic order	Maximum permissible Harmonic current
n	A
Odd harmonics	
3	2,30
5	1,14
7	0,77
9	0,40
11	0,33
13	0,21
$15 \leq n \leq 39$	$0,15 \frac{15}{n}$
Even harmonics	
2	1,08
4	0,43
6	0,30
$8 \leq n \leq 40$	$0,23 \frac{8}{n}$

Limits for Class C equipment	
Harmonic order	Maximum permissible harmonic current expressed as a percentage of the input current at the fundamental frequency
n	%
2	2
3	$30 \cdot \lambda *$
5	10
7	7
9	5
$11 \leq n \leq 39$ (odd harmonics only)	3
* λ is the circuit power factor	

5.5. Operating Condition of EUT

Same as Section 3.6. except the test setup replaced by Section 5.2.

5.6. Test Procedure

The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the maximum harmonic components under normal operating conditions for each successive harmonic component in turn. The correspondent test program of test instrument to measure the current harmonics emanated from EUT is chosen. The measure time shall be not less than the necessary for the EUT to be exercised.

5.7. Test Results

EUT power supplies by DC Power, so this item test not applicable.

6. VOLTAGE FLUCTUATIONS & FLICKER TEST

6.1. Test Equipment

Same as Section 5.1.

6.2. Block Diagram of Test Setup

Same as Section 5.2.

6.3. Test Standard

EN 61000-3-3:2013

6.4. Limits of Voltage Fluctuation and Flick

Test Item	Limit	Note
P_{st}	1.0	P_{st} means Short-term flicker indicator
P_{lt}	0.65	P_{lt} means long-term flicker indicator
T_{dt}	0.2	T_{dt} means maximum time that dt exceeds 3%
$d_{max}(\%)$	4%	d_{max} means maximum relative voltage change.
$d_c(\%)$	3%	d_c means relative steady-state voltage change.

6.5. Operating Condition of EUT

Same as Section 5.5.

6.6. Test Procedure

The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the most unfavorable sequence of voltage changes under normal conditions during the flick measurement, the measure time shall include that part of whole operation changes. The observation period for short-term flicker indicator is 10 minutes and the observation period for long-term flicker indicator is 2 hours.

6.7. Test Results

EUT power supplies by DC Power, so this item test not applicable.

7. IMMUNITY PERFORMANCE CRITERIA

Performance Level

The test results shall be classified in terms of the loss of function or degradation of performance of the equipment under test, relative to a performance level by its manufacturer or the requestor of the test, or the agreed between the manufacturer and the purchaser of the product.

Definition related to the performance level:

1. Based on the used product standard
2. Based on the declaration of the manufacturer, requestor or purchaser

Performance criterion A

When seen from the normal viewing distance, the EUT shall operate with no change beyond the manufacturer's specification, in flicker, colour, focus and jitter (except for the power frequency magnetic field test).

Power frequency magnetic field test

For CRT monitors, the following also applies:

The jitter shall be measured using a measuring microscope as specified in 6.6.14 of ISO 9241-3.

The jitter (in mm) shall not exceed the value $\frac{(\text{character height in mm} + 0,3) \times 2,5}{33,3}$ when the CRT monitor is immersed in a continuous magnetic field of 1A/m (r.m.s.) at one of the power frequencies of 50Hz.

Alternatively, a field of 50A/m may be applied, and a transparent graduated mask used to assess the jitter. In that case, the jitter shall not exceed 50 times the value in the above formula.

NOTE-This test level is used to simplify the measurement of jitter. Lesser values of the test level may be used if non-linearity is experienced, due to, for example, saturation of screening material.

The EUT shall be tested in two positions, both perpendicular to the magnetic field.

Performance criterion B

Screen disturbances during the application of the test are permissible.

Performance criterion C


Failures which are not self-recovered after removal of the external disturbance, but which can be recovered to normal operation by reset or reboot are permissible.

8. ELECTROSTATIC DISCHARGE IMMUNITY TEST

8.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	ESD Tester	HAEFELY	PESD1610	H310546	Jan 22, 14	1 Year

8.2. Block Diagram of Test Setup



8.3. Test Standard

EN 55024: 2010(IEC 61000-4-2: 2008)
(Severity Level 1 & 2 & 3 for Air Discharge at 2 kV & 4 kV & 8kV,
Severity Level 1 & 2 for Contact Discharge at 2 kV & 4kV)

8.4. Severity Levels and Performance Criterion

8.4.1. Severity level

Level	Test Voltage Contact Discharge (kV)	Test Voltage Air Discharge (kV)
1.	2	2
2.	4	4
3.	6	8
4.	8	15
X	Special	Special

8.4.2. Performance criterion : **B**

8.5. EUT Configuration

The configurations of EUT are listed in Section 3.5.

8.6. Operating Condition of EUT

Same as Conducted Emission test that is listed in Section 3.6. except the test set up replaced by Section 8.2.

8.7. Test Procedure

8.7.1. Air Discharge:

The test was applied on non-conductive surfaces of EUT. The round discharge tip of the discharge electrode was approached as fast as possible to touch the EUT. After each discharge, the discharge electrode was removed from the EUT. The generator was re-triggered for a new single discharge and repeated 20 times for each pre-selected test point. This procedure was repeated until all the air discharge completed

8.7.2. Contact Discharge:

All the procedure was same as Section 8.7.1. except that the generator was re-triggered for a new single discharge and repeated 50 times for each pre-selected test point. The tip of the discharge electrode was touching the EUT before the discharge switch was operated.

8.7.3. Indirect discharge for horizontal coupling plane:

At least 20 single discharges were applied to the horizontal coupling plane, at points on each side of the EUT. The discharge electrode positions vertically at a distance of 0.1m from the EUT and with the discharge electrode touching the coupling plane.

8.7.4. Indirect discharge for vertical coupling plane:

At least 20 single discharges were applied to the center of one vertical edge of the coupling plane. The coupling plane, of dimensions 0.5m X 0.5m, was placed parallel to, and positioned at a distance of 0.1m from the EUT. Discharges were applied to the coupling plane, with this plane in sufficient different positions that the four faces of the EUT are completely illuminated.

8.8. Test Results

PASS.

The EUT was tested and all the test results are listed in next page.

Electrostatic Discharge Test Results

Applicant	:	China Etech Groups Ltd	Test Date	:	December 17, 2014
EUT	:	Car charger	Temperature	:	24°C
M/N	:	ECC014	Humidity	:	56%
Test Voltage	:	DC 12V From Battery	Test Mode	:	Full Load
Test Engineer	:	Reak	Pressure	:	101.3KPa
Required Performance	:	B	Actual Performance	:	B

Air Discharge: $\pm 2\text{kV}$ $\pm 4\text{kV}$ $\pm 8\text{kV}$ # For Air Discharge each Point Positive 25 times and negative 25 times discharge.

Contact Discharge: $\pm 2\text{kV}$ $\pm 4\text{kV}$ # For Contact Discharge each point positive 25 times and negative 25 times discharge

For the time interval between successive single discharges an initial value of one second.

Discharge Voltage (kV)	Type of discharge	Dischargeable Points	Performance		Result (Pass/Fail)
			Required	Observation	
± 2	Contact	1,3	B	B	Pass
± 4	Contact	1,3	B	B	Pass
± 2	Air	2	B	B	Pass
± 4	Air	2	B	B	Pass
± 8	Air	2	B	B	Pass
± 2	HCP-Bottom	Edge of the HCP	B	A	Pass
± 2	VCP-Front	Center of the VCP	B	A	Pass
± 2	VCP-Left	Center of the VCP	B	A	Pass
± 2	VCP-Back	Center of the VCP	B	A	Pass
± 2	VCP-Right	Center of the VCP	B	A	Pass
± 4	HCP-Bottom	Edge of the HCP	B	A	Pass
± 4	VCP-Front	Center of the VCP	B	A	Pass
± 4	VCP-Left	Center of the VCP	B	A	Pass
± 4	VCP-Back	Center of the VCP	B	A	Pass
± 4	VCP-Right	Center of the VCP	B	A	Pass

Discharge Points Description

<u>1</u>	Metal	<u>6</u>	
<u>2</u>	Slots	<u>7</u>	
<u>3</u>	USB port	<u>8</u>	
<u>4</u>		<u>9</u>	
<u>5</u>		<u>10</u>	

Test Equipment: ESD Tester (PESD1610)

Remark: 1. Class A is no function loss.

2. Class B is EUT slight change in voltage, but it can automatically reply.


Discharge was considered on Contact and Air and Horizontal Coupling Plane (HCP) and Vertical Coupling Plane (VCP).

9. RF FIELD STRENGTH SUSCEPTIBILITY TEST

9.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Signal Generator	Marconi	2031B	11606/058	Jan 20, 14	1 Year
2.	Amplifier	A&R	100W/1000M1	17028	NCR	NCR
3.	Isotropic Field Monitor	A&R	FM7004	0325983	NCR	NCR
4.	Isotropic Field Probe	A&R	FL7006	0325736	Jan 20, 14	1 Year
5.	Laser Probe Interface	A&R	FL7000	325430	NCR	NCR
6.	Power Meter	Anritsu	ML2487A	6k00003262	Jan 20, 14	1Year
7.	Power Sensor	Anritsu	MA2491A	33005	Jan 20, 14	1Year
8.	Log-periodic Antenna	A&R	AT1080	16512	NCR	NCR

9.2. Block Diagram of Test Setup



9.3. Test Standard

EN 55024: 2010(IEC 61000-4-3:2006+A1: 2007+A2: 2010)
(Severity Level: 2 at 3V / m)

9.4. Severity Levels and Performance Criterion

9.4.1. Severity level

Level	Test Field Strength V/m
1.	1
2.	3
3.	10
X	Special

9.4.2. Performance criterion: A

9.5. EUT Configuration

The configurations of EUT are listed in Section 3.5.

9.6. Operating Condition of EUT

Same as Conducted Emission test that is listed in Section 3.6. except the test set up replaced by Section 9.2.

9.7. Test Procedure

Testing was performed in a fully anechoic chamber as recommended by IEC 61000-4-3. The EUT was placed on an 80 cm high non-conductive table located in the area of field uniformity. The radiating antenna was placed 3m in front of the EUT and Support system, and dwell time of the radiated interference was controlled by an automated, computer-controlled system. The signal source was stepped through the applicable frequency range at a rate no faster than 1% of the fundamental. The signal was amplitude modulated 80% over the frequency range 80 MHz to 1GHz at a level of 3 V/m. The dwell time was set at 3 s. Field presence was monitored during testing via a field probe placed in close proximity to the EUT. Throughout testing, the EUT was closely monitored for signs of susceptibility. The test was performed with the antennae oriented in both a horizontal and vertical polarization.

All the scanning conditions are as follows:

Condition of Test	Remarks
1. Test Fielded Strength	3 V/m (Severity Level 2)
2. Radiated Signal	80% amplitude modulated with a 1kHz sine wave
3. Scanning Frequency	80 - 1000 MHz
4. Sweeping time of radiated	0.0015 decade/s
5. Dwell Time	3 Sec.

9.8. Test Results

PASS.

The EUT was tested and all the test results are listed in next page.

RF Field Strength Susceptibility Test Results


Applicant	:	China Etech Groups Ltd	Test Date	:	December 17, 2014
EUT	:	Car charger	Temperature	:	24°C
M/N	:	ECC014	Humidity	:	56%
Test Voltage	:	DC 12V From Battery	Test Mode	:	Full Load
Test Engineer	:	Reak	Pressure	:	101.3KPa
Frequency Range	:	80 MHz -1000MHz	Field Strength	:	3V/m
Required Performance	:	A	Actual Performance	:	A
Modulation: <input checked="" type="checkbox"/> AM <input type="checkbox"/> Pulse <input type="checkbox"/> none 1 kHz 80%					
Frequency Range :80 MHz -1000MHz					
Steps	1%				
	Horizontal		Vertical		Result
	Required	Observation	Required	Observation	(Pass / Fail)
Front	A	A	A	A	Pass
Right	A	A	A	A	Pass
Rear	A	A	A	A	Pass
Left	A	A	A	A	Pass
Test Equipment : 1. Signal Generator : Marconi 2031B 2. Power Amplifier : A&R 500A/100;100W/1000M. 3. Power Antenna : A&R AT-1080. 4. Field Monitor : A&R FM7004.					
Remark: Class A is no function loss.					

10. ELECTRICAL FAST TRANSIENT/BURST IMMUNITY TEST

10.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Burst Tester	3ctest	EFT-4001G	EC0461015	Jan 20, 14	1 Year

10.2. Block Diagram of Test Setup



10.3. Test Standard

EN 55024: 2010(IEC 61000-4-4:2012)
(Severity Level 2 at 1kV)

10.4. Severity Levels and Performance Criterion

10.4.1. Severity level

Open Circuit Output Test Voltage $\pm 10\%$		
Level	On Power Supply Lines	On I/O (Input/Output) Signal data and control lines
1.	0.5 kV	0.25 kV
2.	1 kV	0.5 kV
3.	2 kV	1 kV
4.	4 kV	2 kV
X	Special	Special

10.4.2. Performance criterion : B

10.5. EUT Configuration

The configurations of EUT are listed in Section 3.5.

10.6. Operating Condition of EUT

Same as Conducted Emission test that is listed in Section 3.6. except the test set up replaced by Section 10.2.

10.7. Test Procedure

The EUT and its simulators were placed on the ground reference plane and were insulated from it by a wood support $0.1\text{m} \pm 0.01\text{m}$ thick. The ground reference plane was $1\text{m} \times 1\text{m}$ metallic sheet with 0.65mm minimum thickness. This reference ground plane was project beyond the EUT by at least 0.1m on all sides and the minimum distance between EUT and all other conductive structure, except the ground plane was more than 0.5m. All cables to the EUT was placed on the wood support, cables not subject to EFT/B was routed as far as possible from the cable under test to minimize the coupling between the cables.

10.7.1. For input and AC power ports:

The EUT was connected to the power mains by using a coupling device that couples the EFT interference signal to AC power lines. Both positive transients and negative transients of test voltage were applied during compliance test and the duration of the test can't less than 1min.

10.7.2. For signal lines and control lines ports:

It's unnecessary to test.

10.7.3. For DC input and DC output power ports:

It's unnecessary to test.

10.8. Test Results


EUT power supplies by DC Power, so this item test not applicable.

11. SURGE TEST

11.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Surge CDN	3ctest	SGN-5010G	EC5591004	Jan 20, 14	1 Year
2.	Surge Generator	3ctest	SG-5006G	EC5581006	Jan 20, 14	1 Year

11.2. Block Diagram of Test Setup



11.3. Test Standard

EN 55024: 2010 (IEC 61000-4-5: 2005)
(Severity Level: Line to Line was Level 2 at 1kV)

11.4. Severity Levels and Performance Criterion

11.4.1. Severity level

Severity Level	Open-Circuit Test Voltage kV
1	0.5
2	1.0
3	2.0
4	4.0
*	Special

11.4.2. Performance criterion: **B**

11.5. EUT Configuration

The configurations of EUT are listed in Section 3.5.

11.6. Operating Condition of EUT

Same as Conducted Emission test that is listed in Section 3.6. except the test set up replaced by Section 11.2

11.7. Test Procedure

- 1) Set up the EUT and test generator as shown on Section 11.2.
- 2) For line-to-line coupling mode, provide a 1kV 1.2/50us voltage surge (at open-circuit condition) and 8/20us current surge to EUT selected points, and for active line / neutral lines to ground are same except test level is 2kV.
- 3) At least 5 positive and 5 negative (polarity) tests with a maximum 1/min repetition rate are applied during test.
- 4) Different phase angles are done individually.
- 5) Record the EUT operating situation during compliance test and decide the EUT immunity criterion for above each test.

11.8. Test Results


EUT power supplies by DC Power, so this item test not applicable.

12. INJECTED CURRENTS SUSCEPTIBILITY TEST

12.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Conducted Immunity Test System	Frankonia	CIT-10/75	12681247/2013	Jan 20, 14	1 Year
2.	Fixed Coaxial Attenuator	CD	ATT-0675	120540086	Jan 20, 14	1 Year
3.	coupling-decoupling network (CDN)	CD	CDN M2/M3	2302	Jan 20, 14	1 Year
4.	Electromagnetic Injection Clamp (EMC-Clamp)	CD	EM-Clamp	0513A031201	Jan 20, 14	1 Year

12.2. Block Diagram of Test Setup



12.3. Test Standard

EN 55024: 2010 (IEC61000-4-6: 2008)

(Severity Level 2 at 3V (r.m.s.) and frequency is from 0.15MHz to 80MHz)

12.4. Severity Levels and Performance Criterion

12.4.1. Severity level

Level	Voltage Level (e.m.f.) V
1.	1
2.	3
3.	10
X	Special

12.4.2. Performance criterion: A

12.5. EUT Configuration

The configurations of EUT are listed in Section 3.5.

12.6. Operating Condition of EUT

Same as Conducted Emission test that is listed in Section 3.6. except the test set up replaced by Section 12.2.

12.7. Test Procedure

- 1) Set up the EUT, CDN and test generators as shown on Section 12.2.
- 2) Let the EUT work in test mode and test it.
- 3) The EUT are placed on an insulating support 0.1m high above a ground reference plane. CDN (coupling and decoupling device) is placed on the ground plane about 0.3m from EUT. Cables between CDN and EUT are as short as possible, and their height above the ground reference plane shall be between 10 and 30 mm (where possible).
- 4) The disturbance signal described below is injected to EUT through CDN.
- 5) The EUT operates within its operational mode(s) under intended climatic conditions after power on.
- 6) The frequency range is swept from 0.150MHz to 80MHz using 3V signal level, and with the disturbance signal 80% amplitude modulated with a 1kHz sine wave.
- 7) The rate of sweep shall not exceed 1.5×10^{-3} decades/s. Where the frequency is swept incrementally, the step size shall not exceed 1% of the start and thereafter 1% of the preceding frequency value.
- 8) Recording the EUT operating situation during compliance testing and decide the EUT immunity criterion.

12.8. Test Results


EUT power supplies by DC Power, so this item test not applicable.

13. MAGNETIC FIELD IMMUNITY TEST

13.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Magnetic Field Tester	HEAFELY	MAG100.1	083858-10	Jan 20, 14	1 Year

13.2. Block Diagram of Test Setup



13.3. Test Standard

EN 55024: 2010 (IEC 61000-4-8: 2009)
(Severity Level 1 at 1A/m)

13.4. Severity Levels and Performance Criterion

13.4.1. Severity level

Level	Magnetic Field Strength A/m
1.	1
2.	3
3.	10
4.	30
5.	100
X.	Special

13.4.2. Performance criterion : A

13.5. EUT Configuration on Test

The configurations of EUT are listed in Section 3.5.

13.6. Operating Condition of EUT

Same as Conducted Emission test that is listed in Section 3.6. except the test set up replaced by Section 13.2.

13.7. Test Procedure

The EUT was subjected to the test magnetic field by using the induction coil of standard dimensions (1m*1m) and shown in Section 13.2. The induction coil was then rotated by 90° in order to expose the EUT to the test field with different orientations.

13.8. Test Results


The EUT not containing device susceptible to magnetic fields, and Power-frequency magnetic field test applicable only to EUT containing devices susceptible to magnetic fields, so the test not applicable.

14. VOLTAGE DIPS AND INTERRUPTIONS TEST

14.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Main Interference Simulator	3ctest	VDG-1105G	EC0171002	Jan 20, 14	1 Year

14.2. Block Diagram of Test Setup



14.3. Test Standard

EN 55024: 2010 (IEC 61000-4-11: 2004)

14.4. Severity Levels and Performance Criterion

14.4.1. Severity level

Test Level $\%U_T$	Voltage dip and short interruptions $\%U_T$	Performance Criterion	Duration (in period)
0	100	C	250
0	100	B	0.5
30	70	C	25

14.4.2. Performance criterion : B & C

14.5. EUT Configuration

The configurations of EUT are listed in Section 3.5.

14.6. Operating Condition of EUT

Same as Conducted Emission test that is listed in Section 3.6. except the test set up replaced by Section 14.2.



14.7. Test Procedure


- 1) The EUT and test generator were setup as shown on Section 14.2.
- 2) The interruption is introduced at selected phase angles with specified duration.
- 3) Record any degradation of performance.

14.8. Test Results


EUT power supplies by DC Power, so this item test not applicable.

15. PHOTOGRAPHS

15.1. Photos of Radiated Emission Test (In Anechoic Chamber)



15.2. Photos of Electrostatic Discharge Immunity Test




16. PHOTOS OF THE EUT




Front View




Rear View




Left View




Right View




Top View



Bottom View



Inside View



Inside View

-----THE END OF REPORT-----