



TEST REPORT

ETSI EN62479:2010

Product : Wireless sport earbuds

Model Name : P326.23X

Brand : N/A

Report No. : PTCHX04161101902E-EM03

Prepared for

Prepared by

DongGuan Precise Testing Service Co.,Ltd.

Building D, Baoding Technology Park, Guangming Road 2, Guangming Community

Dongcheng District, Dongguan, Guangdong, China



TEST RESULT CERTIFICATION

Applicant's name	:			
Address	:			
Manufacture's name	:			
Address	:			
Product name	: Wireless sport	earbuds		
Model name	: P326.23X			
This device described abov under test (EUT) is in comp applicable only to the tested	oliance with the 2014/	53/EU R&TTE Directive		
This report shall not be repr may be altered or revised b				
Date of Test				
Date (s) of performance	of tests :	November 28, 2016 -	- December 7,	2016
Date of Issue:		December 7, 2016		
Test Result:		Pass		
Tested By:			Auguse	Qiu
Approved & Authorized S	Signer		August Qiu / PR	OVED



Contents

			Page
2	TES	T SUMMARY	4
3	GEN	IERAL INFORMATION	5
	3.1	GENERAL DESCRIPTION OF E.U.T	5
4	RF EXPOSURE EVALUATION		6
	4.1	LIMITS	6
	4.2	TEST RESULT OF RF EXPOSURE EVALUATION	6



2 Test Summary

Test	Test Requirement	Test Method	Limit / Severity	Result
RF Exposure	EN 62479	EN 62479	-	PASS

Remark:

N/A: Not Applicable

RF: In this whole report RF means Radio Frequency.

A.M. Amplitude Modulation.

P.M. Pulse Modulation.



3 General Information

3.1 General Description of E.U.T.

Product Name : Wireless sport earbuds

Model Name P326.23X

Model Description : N/A

Operation Frequency: 2.40~2.483GHz

Antenna installation: : Integrated Antenna

Antenna Gain: : 0dBi

Type of Modulation : ASK

Power supply : 5V 100mah-1A



4 RF Exposure Evaluation

4.1 Limits

According to Council Recommendation: the criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation.

Reference levels for electric, magnetic and electromagnetic fields (10MHz to 300GHz)

Low-power electronic and electrical equipment is deemed to comply with the provisions of this standard if it can be demonstrated using routes B, C or D that the available antenna power and/or the average total radiated power is less than or equal to the applicable low-power exclusion level Pmax.

Annex A contains example values for Pmax derived from existing exposure limits listed in the bibliography, such as the ICNIRP guidelines [1], IEEE Std C95.1-1999 [2], and IEEE Std C95.1-2005 [3].

For wireless devices operated close to a person's body with available antenna powers and/or average total radiated powers higher than the Pmax values given in Annex A, the alternative Pmax values (called Pmax'), described in Annex B can also be used.

For low power equipment using pulsed signals, other limits may apply in addition to those considered in Annex A and Annex B. Both ICNIRP guidelines [1] and IEEE standards [2], [3] have specific restrictions on exposures to pulsed fields, and the requirements of those standards with respect to exposure to pulses shall be met. Annex C discusses this topic further.

4.2 Test Result of RF Exposure Evaluation

Test Mode	Transmit
Limit (Pmax)	20mW/13dBm

After performed the test at low/middle/high channel, the below recorded is the worst.

Max. Peak Output Power (dBm)	Pmax (dBm)
-3.26	14

Remark:Since the max. peak output power is less than the applicable low-power exclusion level Pmax,this device is deemed to comply with the provisions of this standard without further testing.

*****THE END REPORT*****