

RF Test Report

Report No.: AGC01978180106EE17

PRODUCT DESIGNATION : Portfolio with wireless power bank

BRAND NAME : N/A

MODEL NAME : P773.881

MANUFACTURER : Xindao B.V.

DATE OF ISSUE : Mar. 14, 2018

STANDARD(S) : ETSI EN 303 417 V1.1.1(2017-09)

REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd.

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Mar. 14, 2018	Valid	Initial Release

Note: Based on the report No.: AGC01978180105EE17, this report changed the information of the model name and appearance of the end product.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION.....	3
2. EUT DESCRIPTION.....	4
3. DESCRIPTION OF TEST ITEMS.....	5
4. TEST FACILITY	5
5. ETSI EN 303 417 REQUIREMENT	6
5.1 TRANSMITTER H-FIELD REQUIREMENTS	6
5.2 OPERATING FREQUENCY RANGES	9
5.3 TRANSMITTER OUT OF BAND (OOB) EMISSIONS	11
5.4 TRANSMITTER SPURIOUS EMISSIONS	14
5.5 RECEIVER BLOCKING	19
6. INTERPRETATION OF MEASUREMENT RESULTS.....	21
APPENDIX 1: PHOTOGRAPHS OF TEST SETUP.....	22

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

1. TEST RESULT CERTIFICATION

Manufacturer	Xindao B.V.
Address	VERRIJN STUARTLAAN 1D 2288EK RIJSWIJK NETHERLANDS
Factory	
Address	
Product Designation	Portfolio with wireless power bank
Brand Name	N/A
Test Model	P773.881
Date of test	Mar. 12, 2018 to Mar. 14, 2018
Deviation	None
Condition of Test Sample	Normal
Test Result	Pass
Report Template	AGCRT-EC-EMC

The above equipment was tested by SHENZHEN ATTESTATION OF GLOBAL COMPLIANCE (SHENZHEN) CO., LTD. for compliance with the requirements set forth in the European Standard ETSI EN 303 417 V1.1.1. The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested by

Max Zhang

Max Zhang(Zhang Yi)

Mar. 14, 2018

Reviewed by

Bart Xie

Bart Xie(Xie Xiaobin))

Mar. 14, 2018

Approved By

Forrest Lei

Forrest Lei(Lei Yonggang)

Mar. 14, 2018

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

2. EUT DESCRIPTION

Details of technical specification refer to the description in follows:

Hardware Version	G006_A V1.1, G006B_A V1.1
Software Version	V1.0
The permitted range of operating frequencies used	110-205KHz
Test Frequency	178KHz
Number of Channels	1 Channel
Antenna Type	Integral antenna
Operational Mode	Mode 3: communication Mode 4: energy transmission
Power Supply	DC 3.7V

NOTE: For more information, please refer to User's Manual.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

3. DESCRIPTION OF TEST ITEMS

Harmonised Standard ETSI EN 303 417		
Requirement		Requirement Conditionality
No	Description	
1	Permitted range of operating frequencies	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable
2	Operating frequency ranges	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable
3	H-field requirements	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable
4	Transmitter spurious emissions	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable
5	Transmitter out of band (OOB) emissions	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable
6	WPT system unwanted conducted emissions	<input type="checkbox"/> Applicable <input checked="" type="checkbox"/> Not Applicable
7	Receiver blocking	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable

4. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	B112-B113, Building 12, Baoan Building Materials Center, No.1 of Xixiang Inner Ring Road, Baoan District, Shenzhen, Guangdong, P.R.China

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.


5. ETSI EN 303 417 REQUIREMENT

5.1 TRANSMITTER H-FIELD REQUIREMENTS

MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	100096	June. 29, 2017	June. 28, 2018
Amplifier	EM	EM30180	060552	June. 29, 2017	June. 28, 2018
Loop Antenna	A.H.	SAS-526B	--	Mar. 01, 2018	Feb. 28, 2019

TEST SETUP:



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

TEST LIMITS:

The H-field limit in dBμA/m at 3 m, H_{3m} , is determined by the following equation:

$$H_{3m} = H_{10m} + C_3 \text{ (F.2)}$$

Where: H_{10m} is the H-field limit in dBμA/m at 10 m distance according to the present document; and C_3 is a conversion factor in dB determined from figure F.2.

The limit at 10 m(H_{10m}) is -5 dBμA/m.

Owing to the frequency EUT is 164.5kHz, so the C_3 approach to 31.5dB.

Then the limit at 3m(H_{3m}) = $H_{10m} + C_3 = -5 + 31.5 = 26.5$ dBμA/m.

The H Field Strength shall not exceed the values 26.5 dBuA/m 3m Distance under normal test conditions.

Correction factor, C_3 , for limits at 3 m distance, dB




Figure F.2: Conversion factor C_3 versus frequency

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

TEST PROCEDURE:

The EUT was placed on the top of an insulating table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

The H-field is measured with a shielded loop antenna connected to a measurement receiver.

The measuring bandwidth and detector type of the measurement receiver shall be in accordance with EN 300 330 V2.1.1 Table 11.

The EUT operate with modulation under normal and extreme conditions.

TEST RESULTS:

Test Mode: Mode 4

Extreme conditions state

conditions	Test Temp	Test Volt.(V)	Note
TN/VN	25°C	3.70	Worst case
TL/ VL	-10°C	3.15	
TH/VL	45°C	3.15	
TL/VH	-10°C	3.70	
TH/VH	45°C	3.70	

Test results tested at 3m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.178	23.54	-17.55	5.99	26.5

Test results calculated to 10m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.178	23.54	-49.05	-25.51	-5

Remark:

- (1) Corrected Level (dBuA/m) = Reading Level + Antenna Factor
- (2) For the calculated method, please refer to Annex F at EN 300330.
- (3) All extreme conditions were considered for test, but only record the worst case.


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

5.2 OPERATING FREQUENCY RANGES

MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	100096	June. 29, 2017	June. 28, 2018
Amplifier	EM	EM30180	060552	June. 29, 2017	June. 28, 2018
Loop Antenna	A.H.	SAS-526B	--	Mar. 01, 2018	Feb. 28, 2019

TEST SETUP:



TEST PROCEDURE:

- 1). The EUT was placed on a turn table which is 0.8m above ground plane.
- 2). The EUT was modulated by normal signal,
- 3). Set SPA Center Frequency = fundamental frequency, RBW=VBW=200Hz, Span=5kHz, Detector=RMS. The 99 % OBW function shall be used to determine the operating frequency range, fH is the frequency of the upper marker resulting from the OFR, fL is the frequency of the lower marker resulting from the OFR.
- 4). Both normal test condition and extreme test condition applied

LIMITS

The operating frequency range for emissions shall be within one of the following limits: 19 - 21 kHz, 59 - 61 kHz, 79 - 90 kHz, 100 - 300 kHz, 6 765 - 6 795 kHz.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

TEST RESULT

Frequency Range Test Result

Test Temperature	Test Voltage (V DC)	Upper Frequency (kHz)	Lower Frequency (kHz)	Limit
-10°C	3.15	177.422	178.571	100kHz≤&≤300kHz
	3.70	177.421	178.574	100kHz≤&≤300kHz
25°C	3.70	177.422	178.572	100kHz≤&≤300kHz
45°C	3.15	177.422	178.571	100kHz≤&≤300kHz
	3.70	177.424	178.577	100kHz≤&≤300kHz
Results		PASS		

NOTE: All the modes had been tested, but only the worst data recorded in the report.


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

5.3 TRANSMITTER OUT OF BAND (OOB) EMISSIONS

MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	100096	June. 29, 2017	June. 28, 2018
Amplifier	EM	EM30180	060552	June. 29, 2017	June. 28, 2018
Loop Antenna	A.H.	SAS-526B	--	Mar. 01, 2018	Feb. 28, 2019

TEST SETUP:



TEST PROCEDURE:

- 1). The EUT was placed on a turn table which is 0.8m above ground plane.
- 2). The EUT was modulated by normal signal,
- 3). Set SPA Center Frequency = fundamental frequency, RBW=VBW=200Hz, Span=5KHz, Detector=RMS. The 99 % OBW function shall be used to determine the operating frequency range, fH is the frequency of the upper marker resulting from the OFR, fL is the frequency of the lower marker resulting from the OFR.
- 4). Both normal test condition and extreme test condition applied

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

LIMITS

The OOB limits are visualized in figures; they are descending from the intentional limits from Table 3 at f_H/f_L with 10 dB/decade.




Figure 4: Out of band and spurious domain of a single frequency WPT system

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

TEST RESULT

Frequency range (KHz)		Limit(dbuA/m)	Result
fSL -fL	175.5KHz-177.5KHz	See figure 4	Pass
fL	177.5KHz	-5	Pass
fH	178.5KHz	-5	Pass
fH - fSH	178.5KHz-180.5KHz	See figure 4	Pass

NOTE: All the modes had been tested, but only the worst data recorded in the report.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.


5.4 TRANSMITTER SPURIOUS EMISSIONS

MEASUREMENT EQUIPMENT USED:


NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	100096	June. 29, 2017	June. 30, 2018
Amplifier	EM	EM30180	060552	June. 29, 2017	June. 30, 2018
Loop Antenna	A.H.	SAS-526B	--	Mar. 01, 2018	Feb. 28, 2019
ANTENNA	SCHWARZBECK	VULB9168	494	Mar. 01, 2018	Feb. 28, 2019

TEST SETUP:

FREQUENCY RANGE (9KHZ-30MHZ)




FREQUENCY RANGE (ABOVE 30MHZ)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

**SUBSTITUTION METHOD:
RADIATED BELOW 1GHZ**



TEST PROCEDURE:

For test method of frequency range (9 kHz-30MHz)

The EUT was placed on the top of an insulating table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

The H-field is measured with a shielded loop antenna connected to a measurement receiver.

The measuring bandwidth and detector type of the measurement receiver shall be in accordance with EN 300 330 Table 1.

For test method of frequency range (30 MHz-1000MHz)

EUT was placed on a 1.5m height wooden table. The search antenna is placed at 3m distances from the EUT and search antenna height is from 1-4m. With the transmitter operating at continuously mode, the turntable was slowly rotated to locate the direction of maximum emission. Once maximum direction is determined, the search antenna was raised and lowered in both vertical and horizontal polarizations.

The EUT was removed from the turntable and replaced with a linearly polarized antenna connected to a calibrated RF signal generator. The RF generator was set to a measured emission frequency and the search antenna was raised and lowered to produce a maximum received reading. The generator output was increased to match the radiated emission reading measured previously, and the result expressed in dB EIRP or ERP, correcting for substitution antenna gain at each frequency.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

LIMITS OF RADIATED DISTURBANCES

Below 30MHz

Table 4

State (see note)	Frequency $9 \text{ kHz} \leq f < 10 \text{ MHz}$	Frequency $10 \text{ MHz} \leq f < 30 \text{ MHz}$
Operating	27 dB μ A/m at 9 kHz descending 10 dB/dec	-3,5 dB μ A/m
Standby	5,5 dB μ A/m at 9 kHz descending 10 dB/dec	-25 dB μ A/m
NOTE: "Operating" means mode 2, 3 and 4 according to Table 2; "standby" means mode 1 according to Table 2.		

Table 5

State (see note)	47 MHz to 74 MHz 87,5 MHz to 118 MHz 174 MHz to 230 MHz 470 MHz to 790 MHz	Other frequencies between 30 MHz to 1 000 MHz
Operating	4 nW	250 nW
Standby	2 nW	2 nW
NOTE: "Operating" means mode 2, 3 and 4 according to Table 2; "standby" means mode 1 according to Table 2.		

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

TEST LIMITS & RESULT

FREQUENCY RANGE (9KHZ-30MHZ)

OPERATION MODE					
Frequency	Reading level	Total Factor	Emission level	10M Limit	Margin
(MHz)	(dBμA/m)	(dB)	(dB μA/m)	(dBμA/m)	(dBμA/m)
--	--	--	--	27 dBμA/m at 9KHz descending 10dB/dec (9KHz – 10MHz)	--
--	--	--	--		--
--	--	--	--	-3.5 dBμA/m(10MHz – 30MHz)	--
--	--	--	--		--

Remark:

- (1) Corrected Power (dBm) = Total Factor + Reading Level
- (2) Measuring frequencies from 9KHz to the 30MHz.

- (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

FREQUENCY RANGE (ABOVE 30MHZ)

Transmitter Spurious Emission below 1GHz (30MHz-1GHz)

Frequency	Reading Level	Antenna	S.G.	Cable Loss	Ant.Gain	Emission Level	Limit	Margin
(MHz)	(dBuv/m)	Polarization	(dBm)	(dB)	(dBi)	(dBm)	(dBm)	(dB)
77.22	27.73	V	-64.21	0.04	-0.70	-64.95	-36.00	28.95
235.30	29.78	V	-70.02	0.11	6.60	-63.53	-36.00	27.53
379.02	28.14	V	-70.87	0.28	6.51	-64.64	-36.00	28.64
388.11	30.30	V	-68.40	0.29	6.42	-62.26	-36.00	26.26
425.87	26.99	V	-73.30	0.33	7.00	-66.64	-36.00	30.64
827.42	31.43	V	-67.75	0.66	6.45	-61.95	-54.00	7.95
140.46	32.18	H	-60.93	0.05	0.00	-60.98	-36.00	24.98
339.10	32.63	H	-66.93	0.23	5.74	-61.42	-36.00	25.42
394.90	28.76	H	-70.55	0.30	6.48	-64.36	-36.00	28.36
455.76	27.67	H	-71.51	0.37	6.55	-65.33	-36.00	29.33
613.89	31.61	H	-67.41	0.50	6.62	-61.29	-54.00	7.29
766.43	31.69	H	-67.69	0.62	6.78	-61.52	-54.00	7.52

Note: 1. The margins of the other spectrum are not exceeding the minimum value of margin, and this part of the results without recording in the test report.

2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "--" remark, if no specific emission from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.


The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

5.5 RECEIVER BLOCKING

MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
MXG X-Series Vector Signal Generator	Agilent	N5182B	N/A	Sep. 21, 2017	Sep. 20, 2018
LOOP ANTENNA	LAPLACE	RF300	N/A	Mar. 01, 2017	Feb. 28, 2018
Clamp meter	PROVA	PROVA-11	17200101	Oct. 09, 2017	Oct. 08, 2018

TEST SETUP:



TEST PROCEDURE:

- 1). The test shall be carried out inside a test chamber according to clauses C.1.1 and C.1.2 in ETSI EN 300 330
- 2). A test loop with a radius r shall be used to create the magnetic field; the test loop shall lie on a non-metallic ground and the minimum distance to metallic objects (e.g. ground plane) shall be 0,75 m. The EUT shall be placed to the centre of the test-loop
- 3). The test loop shall be sufficiently large so that the test loop itself does not influence the WPT system; The radius R of the test-loop shall be in minimum $\Delta R = 0,75\text{ m}$ larger than the maximum dimension r of the EUT.

$$R \geq r + \Delta R.$$

The maximum H-Field can be calculated from the loop current I (into the test-loop) with the following formula:

$$H=I/2R$$

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

4) The required output current to achieve the required magnetic field at the WPT system shall be generated with a signal generator (unmodulated signal) at the test frequencies. For each test frequency the "reaction" of the device shall be recorded and checked against the performance criterion

LIMITS

The EUT shall achieve the wanted performance criterion, in the presence of the blocking signal.

Table 6: Receiver blocking limits

	In-band signal	OOB signal	Remote-band signal
Frequency	Centre frequency (f_c) of the WPT system (see clause 4.3.3)	$f = f_c \pm F$ (see note)	$f = f_c \pm 10 \times F$ (see note)
Signal level field strength at the EUT	72 dB μ A/m	72 dB μ A/m	82 dB μ A/m
NOTE: $F = OFR$ see clause 4.3.3.			

TEST RESULT

Test Mode: Mode 3

Test Frequency(KHz)		Performance	Result
In-band signal	119.5	No function loss	Pass
OOB signal	118.5	No function loss	Pass
	120.5	No function loss	Pass
Remote-band signal	109.5	No function loss	Pass
	129.5	No function loss	Pass

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

6. INTERPRETATION OF MEASUREMENT RESULTS


All the measurement equipments and accessories have been carefully selected to meet the maximum measurement uncertainty specified below:

RF Frequency	$\pm 1 \times 10^{-7}$
RF Power, Conducted	$\pm 0.75\text{dB}$
Maximum Frequency Deviation: _ Within 300Hz and 6KHz of Audio Frequency _ Within 6KHz and 25KHz of Audio Frequency	$\pm 5\%$ $\pm 3\text{dB}$
Adjacent channel power	$\pm 3\text{dB}$
Conducted Emission of Transmitter, Valid Up to 12.75GHz	$\pm 4\text{dB}$
Conducted Emissions of Receivers	$\pm 3\text{dB}$
Radiated Emission of Transmitter, Valid Up to 12.75GHz	$\pm 6\text{dB}$

P.S. Uncertainty figures are valid to confidence level of 95% calculated according to the methods described in the ETSI TR 100 028.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.

APPENDIX 1: PHOTOGRAPHS OF TEST SETUP RADIATED EMISSION TEST



----END OF REPORT----

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at <http://www.agc-cert.com>.