

RADIO TEST REPORT

For

Wireless charger

Test Model: CD-1030

Additional Model No.: /

Prepared for
Address:
:Prepared by
Address:
: Shenzhen LCS Compliance Testing Laboratory Ltd.
: 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an
Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : May 17, 2018

Number of tested samples : 1

Serial number : Prototype

Date of Test : May 18, 2018~ May 22, 2018

Date of Report : May 24, 2018



RADIO TEST REPORT**Final draft ETSI EN 303 417 V1.1.1 (2017-06)**

Wireless power transmission systems, using technologies other than radio frequency beam, in the 19 - 21 kHz, 59 - 61 kHz, 79 - 90 kHz, 100 - 300 kHz, 6 765 - 6 795 kHz ranges; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU

Report Reference No. : LCS180517021AEA

Date Of Issue : May 24, 2018

Testing Laboratory Name : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China

Testing Location/Procedure..... : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □

Applicant's Name :

Address :

Test Specification

Standard..... : Final draft ETSI EN 303 417 V1.1.1 (2017-06)

Test Report Form No. : LCSEMC-1.0

TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2017-06

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description..... : Wireless charger

Trade Mark..... : N/A

Test Model..... : CD-1030

Power Supply : Input: 5V, 3A
 : Output1: 5V, 1A
 : Output2: 5V, 1A

Result : Positive

Compiled by:

Peter Xiao

Peter Xiao / File administrators

Supervised by:

Dick Su

Dick Su/ Technique principal

Approved by:



Gavin Liang/ Manager

EMC -- TEST REPORT

Test Report No. : LCS180517021AEAMay 24, 2018

Date of issue

Test Model..... : CD-1030

EUT..... : Wireless charger

..

Applicant..... :

.

Address..... :

.

Telephone..... : /

.

Fax..... : /

.

Manufacturer..... :

..

Address..... :

.

Telephone..... : /

.

Fax..... : /

.

Factory..... :

.

Address..... :

.

Telephone..... : /

.

Fax..... : /

.

Test Result**Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Revision	Issue Date	Revisions	Revised By
000	May 24,2018	Initial Issue	Gavin Liang

TABLE OF CONTENTS

1. GENERAL INFORMATION	7
1.1. PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	7
1.2. SUPPORT EQUIPMENT LIST	7
1.3. EXTERNAL I/O	7
1.4. OBJECTIVE	8
1.5. TEST METHODOLOGY	8
1.6. MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	8
1.7. DESCRIPTION OF TEST FACILITY	8
1.8. DESCRIPTION OF TEST MODE	8
2. SYSTEM TEST CONFIGURATION.....	9
2.1. JUSTIFICATION	9
2.2. EUT EXERCISE SOFTWARE	9
2.3. SPECIAL ACCESSORIES	9
2.4. BLOCK DIAGRAM/SCHEMATICS	9
2.5. EQUIPMENT MODIFICATIONS	9
2.6. CONFIGURATION OF TEST SETUP	9
3. SUMMARY OF TEST RESULTS.....	10
4. PERMITTED RANGE OF OPERATING FREQUENCIES	11
4.1. DEFINITION	11
4.2. LIMIT	11
4.3. TEST PROCEDURE	11
4.4. TEST RESULT	12
5. OPERATING FREQUENCY RANGE(S) (OFR)	13
5.1. DEFINITION	13
5.2. LIMIT	13
5.3. TEST PROCEDURE	14
5.4. TEST RESULT	14
6. H-FIELD REQUIREMENTS	15
6.1. DEFINITION	15
6.2. LIMIT	15
6.3. TEST SETUP	15
6.4. TEST PROCEDURE	16
6.5. TEST RESULT	16
7. TRANSMITTER SPURIOUS EMISSIONS	18
7.1. DEFINITION	18
7.2. LIMIT	18
7.3. TEST SETUP	19
7.4. TEST PROCEDURE	19
7.5. TEST RESULT	19
8. TRANSMITTER OUT OF BAND (OOB) EMISSIONS.....	21
8.1. DEFINITION	21
8.2. LIMIT	21
8.3. TEST PROCEDURE	21
8.4. TEST RESULT	22
9. WPT SYSTEM UNWANTED CONDUCTED EMISSIONS.....	23
9.1. APPLICABILITY	23
9.2. DEFINITION	23
9.3. LIMIT	23
9.4. TEST PROCEDURE	23
9.4. TEST RESULT	23
10. RECEIVER BLOCKING	24
10.1. DEFINITION	24
10.2. LIMIT	24
10.3. TEST SETUP	24
10.4. TEST PROCEDURE	25

10.5. TEST RESULT 25

11. LIST OF MEASURING EQUIPMENT 26

12.TEST SETUP PHOTOGRAPHS 27

13. EXTERIOR AND INTERIOR PHOTOGRAPHS OF EUT..... 28

1. GENERAL INFORMATION

1.1. Product Description for Equipment Under Test (EUT)

EUT : Wireless charger

Test Model : CD-1030

List Model No. : /

Model Declaration : /

Power Supply : Input: 5V, 3A
Output1: 5V,1A
Output2: 5V, 1A

Hardware version : 1.0

Software version : 1.0

Operating Frequency : 110~205KHz

Modulation Type : FSK

Antenna Description : Coil Antenna, 0 dBi(Max.)

Product class : I

1.2. Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
--	--	--	--	--

1.3. External I/O

I/O Port Description	Quantity	Cable
USB charge Port	1	N/A

1.4. Objective

The following report of is prepared on behalf of the **SHENZHEN UNIWINS TECHNOLOGY CO.,LTD.** in accordance with Final draft ETSI EN 303 417 V1.1.1 (2017-06): Wireless power transmission systems, using technologies other than radio frequency beam, in the 19 - 21 kHz, 59 - 61 kHz, 79 - 90 kHz, 100 - 300 kHz, 6 765 - 6 795 kHz ranges; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU.

The objective is to determine compliance with Final draft ETSI EN 303 417 V1.1.1 (2017-06).

1.5. Test Methodology

All measurements contained in this report were conducted with Final draft ETSI EN 303 417 V1.1.1 (2017-06).

1.6. Measurement Uncertainty (95% confidence levels, k=2)

Test Item	Uncertainty
Radio Frequency	0.9×10^{-4}
Total RF Power, Conducted	1.0 dB
RF Power Density, Conducted	1.8 dB
Spurious Emissions, Conducted	1.8 dB
All Emissions, Radiated	3.1 dB
Temperature	0.5°C
Humidity	1 %
DC And Low Frequency Voltages	1 %

1.7. Description of Test Facility

FCC Registration Number. is 254912.
 Industry Canada Registration Number. is 9642A-1.
 ESMD Registration Number. is ARCB0108.
 UL Registration Number. is 100571-492.
 TUV SUD Registration Number. is SCN1081.
 TUV RH Registration Number. is UA 50296516-001
 NVLAP Registration Code is 600167-0

1.8. Description Of Test Mode

The EUT has been tested under typical operating condition. No software used to control the EUT for staying in transmitting mode for testing.

***Note: The EUT has been tested under normal condition(Temperature: 25°C & Nominal Voltage: DC 5.0V) in this report , and only recorded the worst test data in the report.

2. SYSTEM TEST CONFIGURATION

2.1. Justification

The system was configured for testing in engineering mode.

2.2. EUT Exercise Software

N/A.

2.3. Special Accessories

The special accessories were supplied by Shenzhen LCS Compliance Testing Laboratory Ltd.

2.4. Block Diagram/Schematics

Please refer to the related document.

2.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

2.6. Configuration of Test Setup

Please refer to the test setup photo.

3. SUMMARY OF TEST RESULTS

Reference Clause No.	Description Of Test Item	Result
§4.3.2	Permitted range of operating frequencies	Compliant
§4.3.3	Operating frequency range(s) (OFR)	Compliant
§4.3.4	H-field requirements	Compliant
§4.3.5	Transmitter spurious emissions	Compliant
§4.3.6	Transmitter out of band (OOB) emissions	Compliant
§4.3.7	WPT system unwanted conducted emissions	N/A
§4.4.2	Receiver blocking	Compliant

Note: N/A means not applicable

4. PERMITTED RANGE OF OPERATING FREQUENCIES

4.1. Definition

The permitted range of operating frequencies denotes the frequency ranges set out in Table 1. It likewise denotes the respective frequency range for accommodation of the fundamental WPT frequency of the EUT within its operating frequency range (OFR).

Table 1: WPT systems within the permitted frequency bands below 30MHz

	WPT frequency range	Frequency Bands	WPT systems
Transmit and Receive	1	19 kHz to 21 kHz	WPT systems
Transmit and Receive	2	59 kHz to 61 kHz	WPT systems
Transmit and Receive	3	79 kHz to 90 kHz	WPT systems
Transmit and Receive	4	100 kHz to 119 kHz	WPT systems
Transmit and Receive		119 kHz to 140 kHz	WPT systems
Transmit and Receive		140 kHz to 148,5 kHz	WPT systems
Transmit and Receive		148.5 kHz to 300 kHz	WPT systems
Transmit and Receive	5	6765kHz to 6795 kHz	WPT systems

4.2. Limit


The permitted range of operating frequency range(s) for intentional emissions shall be within 19 - 21 kHz, 59 - 61 kHz, 79 - 90 kHz, 100 - 300 kHz, 6 765 - 6 795 kHz.

Table 2: Overview of operational modes within a WPT system

Operational Mode	Set-up	Function of base station	Function of mobile device	Test scenario	Conformance Requirements
Mode 1: base station in stand-by, idle mode	Single device	Transmitter	Not applicable	Single radiation test (TX) with the base station/charging pad. The test set-up as described in clause 6.1.2 shall be used.	<ul style="list-style-type: none"> Operating frequency range (clause 4.3.3) H-Field emission (clause 4.3.4) TX spurious (clauses 4.3.5, 4.3.6 and 4.3.7) Performance criteria test (RX test) (clause 4.4)
Mode 2: Communication before charging, adjustment charging mode / position	In combination	TX and RX	TX and RX	Specific test setup, declared by the manufacturer. Manufacturer shall declare the maximal distance between base station and mobile device the WPT system is able to communicate (distance D). The test setup- up shall be performed with the largest communication distance. The test set-up as described in clause 6.1.3 shall be used.	<ul style="list-style-type: none"> Operating frequency range (clause 4.3.3) H-Field emission (clause 4.3.4) TX spurious (clauses 4.3.5, 4.3.6 and 4.3.7) Performance criteria test (RX test) (clause 4.4) Wanted performance criteria test (RX test) (clause 4.4)
Mode 3: Communication	WPT system alignment	TX and RX	TX and RX	Worst case alignment	<ul style="list-style-type: none"> Operating frequency range (clause 4.3.3) H-Field emission (clause 4.3.4) TX spurious (clauses 4.3.5, 4.3.6 and 4.3.7) Performance criteria test (RX test) (clause 4.4) Wanted performance criteria test (RX test) (clause 4.4)
Mode 4: energy transmission	WPT system alignment	TX and RX	TX and RX	Both tests can be performed within one set-up, worst-case alignment. The test set-up as described in clause 6.1.4 shall be used.	

4.3. Test Procedure

Please refer to Final draft ETSI EN 303 417 V1.1.1 (2017-06) clause 6 for the measurement method.



4.4. Test Result

Pass

Antenna 0:

Test Result				
Test Temperature (°C)	Test Voltage (Vdc)	Lower Frequency (KHz)	Upper Frequency (KHz)	Limit
25°C	5.0	116.24	200.55	100KHz<f<300KHz
25°C	5.0	118.33	202.48	100KHz<f<300KHz

Antenna 1:

Test Result				
Test Temperature (°C)	Test Voltage (Vdc)	Lower Frequency (KHz)	Upper Frequency (KHz)	Limit
25°C	5.0	116.52	200.69	100KHz<f<300KHz
25°C	5.0	118.48	202.39	100KHz<f<300KHz

5. OPERATING FREQUENCY RANGE(S) (OFR)

5.1. Definition

The operating frequency range is the frequency range over which the WPT system is intentionally transmitting (all operational modes, see clause 4.2.3, Table 2).

The operating frequency range(s) of the WPT system are determined by the lowest (f_L) and highest frequency (f_H) as occupied by the power envelope.

The WPT system could have more than one operating frequency range.

For a single frequency systems the OFR is equal to the occupied bandwidth (OBW) of the WPT system.

For multi-frequency systems the OFR is described in figures 2 and 3.




Figure 2: OFR of a multi - frequency WPT system within one frequency range of Table 2 and within one WPT system cycle time




Figure 3: OFR of a multi - frequency WPT system within two frequency ranges of Table 2 and within one WPT system cycle time

5.2. Limit

The operating frequency range for emissions shall be within one of the following limits: 19 - 21 kHz, 59 - 61 kHz, 79 - 90 kHz, 100 - 300 kHz, 6 765 - 6 795 kHz.

5.3. Test Procedure

Please refer to Final draft ETSI EN 303 417 V1.1.1 (2017-06) clause 6 for the measurement method.

5.4. Test Result

Pass

Antenna 0:

Test Result				
Test Temperature (°C)	Test Voltage (Vdc)	Lower Frequency (KHz)	Upper Frequency (KHz)	Limit
25°C	5.0	116.87	200.76	100KHz<f<300KHz
25°C	5.0	118.65	202.79	100KHz<f<300KHz

Antenna 1:

Test Result				
Test Temperature (°C)	Test Voltage (Vdc)	Lower Frequency (KHz)	Upper Frequency (KHz)	Limit
25°C	5.0	116.59	200.55	100KHz<f<300KHz
25°C	5.0	118.73	202.63	100KHz<f<300KHz

6. H-FIELD REQUIREMENTS

6.1. Definition

The radiated H-field is defined in the direction of maximum field strength under specified conditions of measurement.

6.2. Limit

The H-field limits are provided in Table 3.

They have been specified for control of any radiated emissions within the OFR originating from the WPT system (power transmission and accompanying data communication).

The H-field limits in Table 3 are EU wide harmonised according to EC Decision 2013/752/EU [i.2]. Further information is available in ERC/REC 70-03 [i.1].


Table 3 H-field limits at 10 m

Frequency range [MHz]	H-field strength limit [dB μ A/m at 10 m]	Comments
$0,019 \leq f < 0,021$	72	
$0,059 \leq f < 0,061$	69,1 descending 10 dB/dec above 0,059 MHz	See note 1
$0,079 \leq f < 0,090$	67,8 descending 10 dB/dec above 0,079 MHz	See note 2
$0,100 \leq f < 0,119$	42	
$0,119 \leq f < 0,135$	66 descending 10 dB/dec above 0,119 MHz	See note 1
$0,135 \leq f < 0,140$	42	
$0,140 \leq f < 0,1485$	37,7	
$0,1485 \leq f < 0,30$	-5	
$6,765 \leq f < 6,795$	42	

NOTE 1: Limit is 42 dB μ A/m for the following spot frequencies: 60 kHz \pm 250 Hz and 129,1 kHz \pm 500 Hz.

NOTE 2: At the time of preparation of the present document the feasibility of increased limits for high power wireless power transmission systems to charge vehicles [i.4] was prepared. New specific requirements for such systems (e.g. higher H-field emission limits in the 79 - 90 kHz band) will be reflected within a future revision of the present document.

6.3. Test Setup



6.4. Test Procedure

Please refer to Final draft ETSI EN 303 417 V1.1.1 (2017-06) clause 6.1&6.2 for the measurement method.

6.5. Test Result

Pass

Antenna 0:

Frequency (KHz)	Antenna Polarity	Measure Level At 3m (dBuA/m)	Calculated Factor (dB, -C ₃)	Result At 10m (dBuA/m)	Limit At 10m (dBuA/m)
110.00 (Pairing)	--	7.87	-31.4	-23.53	42.0
111.00	--	10.06	-31.4	-21.34	42.0
114.00	--	9.73	-31.4	-21.67	42.0
117.00	--	10.55	-31.4	-20.85	42.0
120.00	--	9.33	-31.4	-22.07	66 descending 3 dB/oct above 0,119 MHz
129.05	--	0.98	-31.4	-30.42	42.0
129.15	--	1.44	-31.4	-29.96	42.0
135.00	--	8.03	-31.4	-23.37	42.0
139.00	--	8.43	-31.4	-22.97	42.0
141.00	--	7.97	-31.4	-23.43	37.7
148.00	--	7.85	-31.4	-23.55	37.7
150.00	--	8.52	-31.4	-22.88	-5.0
177.50(Low power Mode)	--	2.47	-31.4	-28.93	-5.0
205.00	--	3.40	-31.4	-28.00	-5.0

Antenna 1:

Frequency (KHz)	Antenna Polarity	Measure Level At 3m (dBuA/m)	Calculated Factor (dB, -C ₃)	Result At 10m (dBuA/m)	Limit At 10m (dBuA/m)
110.00 (Pairing)	--	5.16	-31.4	-26.24	42.0
111.00	--	5.71	-31.4	-25.69	42.0
114.00	--	3.94	-31.4	-27.46	42.0
117.00	--	1.23	-31.4	-30.17	42.0
120.00	--	1.55	-31.4	-29.85	66 descending 3 dB/oct above 0,119 MHz
129.05	--	2.84	-31.4	-28.56	42.0
129.15	--	3.54	-31.4	-27.86	42.0
135.00	--	3.46	-31.4	-27.94	42.0
139.00	--	2.86	-31.4	-28.54	42.0
141.00	--	3.38	-31.4	-28.02	37.7
148.00	--	11.66	-31.4	-19.74	37.7
150.00	--	4.16	-31.4	-27.24	-5.0
177.50(Low power Mode)	--	2.47	-31.4	-28.93	-5.0
205.00	--	3.40	-31.4	-28.00	-5.0

***Note:

$$H_{10m}=H_{3m}-C_3$$

The correct factor C₃ is equal to or approximately equal to 31.4dB

All test modes have been tested and only record the worst result.

7. TRANSMITTER SPURIOUS EMISSIONS

7.1. Definition

The transmitter spurious emissions for a single frequency system are to be considered in frequency ranges defined in Figure 4 ($f < f_{SL}$ and $f > f_{SH}$).




Figure 4

7.2. Limit

The radiated field strength of spurious emissions below 30 MHz shall not exceed the generated H-field given in Table 4.

Table 4

State (see note)	Frequency $9 \text{ kHz} \leq f < 10 \text{ MHz}$	Frequency $10 \text{ MHz} \leq f < 30 \text{ MHz}$
Operating	27 dB μ A/m at 9 kHz descending 10 dB/dec	-3,5 dB μ A/m
Standby	5,5 dB μ A/m at 9 kHz descending 10 dB/dec	-25 dB μ A/m

NOTE: "Operating" means mode 2, 3 and 4 according to Table 2; "standby" means mode 1 according to Table 2.

The power of any radiated spurious emission between 30 MHz and 1 GHz shall not exceed the values given in Table 5.

Table 5

State (see note)	47 MHz to 74 MHz 87,5 MHz to 118 MHz 174 MHz to 230 MHz 470 MHz to 790 MHz	Other frequencies between 30 MHz to 1 000 MHz
Operating	4 nW	250 nW
Standby	2 nW	2 nW

NOTE: "Operating" means mode 2, 3 and 4 according to Table 2; "standby" means mode 1 according to Table 2.

7.3. Test Setup

Please refer to Final draft ETSI EN 303 417 V1.1.1 (2017-06) clause 6.

7.4. Test Procedure

Please refer to Final draft ETSI EN 303 417 V1.1.1 (2017-06) clause 6.1&6.2 for the measurement method.

7.5. Test Result

Test Result for Operating Mode (9KHz~30MHz)			
Frequency (MHz)	Measure Level (dBuA/m)	Limit (dBuA/m)	Margin (dB)
--	--	27 dBμA/m at 9 kHz descending 3 dB/oct (9KHz – 10MHz)	--
--	--		--
--	--	-3,5 dBμA/m (10MHz – 30MHz)	--
--	--		--
Test Result for Standby Mode (9KHz~30MHz)			
Frequency (MHz)	Measure Level (dBuA/m)	Limit (dBuA/m)	Margin (dB)
--	--	5.5 dBμA/m at 9 kHz descending 3 dB/oct (9KHz – 10MHz)	--
--	--		--
--	--	-25 dBμA/m (10MHz – 30MHz)	--
--	--		--

Remark:

Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured. Measured in frequency range from 9k~10th harmonic or 1GHz(which is greater).

Antenna 0:

The Test Result for Operating Mode, Tx (Above 30MHz)					
Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Margin (dB)	Pol./Phase	Remark
134.53	-46.92	-36.00	-10.92	Horizontal	Peak
180.42	-68.77	-54.00	-14.77	Horizontal	Peak
838.17	-66.37	-54.00	-12.37	Horizontal	Peak
165.15	-47.25	-36.00	-11.25	Vertical	Peak
117.92	-64.20	-54.00	-10.20	Vertical	Peak
906.54	-46.20	-36.00	-10.20	Vertical	Peak

Antenna 1:

The Test Result for Operating Mode, Tx (Above 30MHz)					
Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Margin (dB)	Pol./Phase	Remark
224.50	-67.09	-54.00	-13.09	Horizontal	Peak
258.18	-47.45	-36.00	-11.45	Horizontal	Peak
804.59	-64.37	-54.00	-10.37	Horizontal	Peak
178.82	-66.88	-54.00	-12.88	Vertical	Peak
298.30	-48.86	-36.00	-12.86	Vertical	Peak
839.01	-64.85	-54.00	-10.85	Vertical	Peak

Note: We have test all modes and only record the worst result.


8. TRANSMITTER OUT OF BAND (OOB) EMISSIONS

8.1. Definition

The WPT system out of band emissions are to be considered in frequency ranges defined in Figure 4 and Figure 5 (between f_{SL} and f_L and between f_H and f_{SH}).

8.2. Limit

The OOB limits are visualized in figures 4 and 5; they are descending from the intentional limits from Table 3 at f_H/f_L with 10 dB/decade.



8.3. Test Procedure

Please refer to Final draft ETSI EN 303 417 V1.1.1 (2017-06) clause 6.1&6.2 for the measurement method.

8.4. Test Result

PASS

Antenna 0:

Frequency (KHz)	Antenna Polarity	Measure Level At 3m (dBuA/m)	Result At 10m (dBuA/m)	Limit At 10m (dBuA/m)
110.00 (Pairing)	--	8.25	-23.15	32.0
111.00	--	10.42	-20.98	32.0
114.00	--	10.13	-21.27	32.0
117.00	--	10.98	-20.42	32.0
120.00	--	9.72	-21.68	56 descending 3 dB/oct above 0,119 MHz
129.05	--	1.34	-30.06	32.0
129.15	--	1.85	-29.55	32.0
135.00	--	8.42	-22.98	32.0
139.00	--	8.86	-22.54	32.0
141.00	--	8.37	-23.03	27.7
148.00	--	8.25	-23.15	27.7
150.00	--	8.87	-22.53	-15.0
177.50(Low power Mode)	--	2.85	-28.55	-15.0
205.00	--	3.79	-27.61	-15.0

Antenna 1:

Frequency (KHz)	Antenna Polarity	Measure Level At 3m (dBuA/m)	Result At 10m (dBuA/m)	Limit At 10m (dBuA/m)
110.00 (Pairing)	--	6.24	-25.42	32.0
111.00	--	8.05	-22.39	32.0
114.00	--	8.36	-24.37	32.0
117.00	--	8.45	-20.17	32.0
120.00	--	8.03	-24.65	56 descending 3 dB/oct above 0,119 MHz
129.05	--	2.63	-31.36	32.0
129.15	--	1.25	-25.87	32.0
135.00	--	9.68	-27.23	32.0
139.00	--	9.33	-23.65	32.0
141.00	--	9.73	-25.38	27.7
148.00	--	7.20	-23.15	27.7
150.00	--	7.65	-22.53	-15.0
177.50(Low power Mode)	--	3.86	-27.36	-15.0
205.00	--	4.56	-25.28	-15.0

9. WPT SYSTEM UNWANTED CONDUCTED EMISSIONS

9.1. Applicability

This applies to all WPT systems where the cable to the primary coil exceeds a length of 3 m and where the cable is not installed in the ground or any metallic structures.

9.2. Definition

WPT system unwanted conducted emissions are based on the emissions of the unwanted common mode current on the cable between the off board power supply and the primary coil seen as a monopole radiator driven against the power supply.

9.3. Limit

The common mode current (ICM) between 1 MHz and 30 MHz shall not exceed the following limit:

$$ICM = 47 - 8 \times \log(f) \text{ dB}\mu\text{A}$$

NOTE: f is the frequency in MHz.

9.4. Test Procedure

Please refer to Final draft ETSI EN 303 417 V1.1.1 (2017-06) clause 6.2.4 for the measurement method.




Figure 9: Measurement setup for unwanted conducted emissions

9.4. Test Result

NOT Applicable.

Note: The EUT cable to the primary coil is less than a length of 3 m.

10. RECEIVER BLOCKING

10.1. Definition

Blocking is a measure of the capability of the receiver to receive a wanted signal without exceeding a given degradation due to the presence of an unwanted input signal at any frequencies other than those of the receiver spurious responses.

The test shall be performed in the relevant operational modes (see clause 4.2.3).

The wanted performance criteria from clause 4.2.2 shall be used as criterion for the receiver blocking tests.

10.2. Limit

Table 6: Receiver blocking limits

	In-band signal	OOB signal	Remote-band signal
Frequency	Centre frequency (fc) of the WPT system (see clause 4.3.3)	$f = f_c \pm F$ (see note)	$f = f_c \pm 10 \times F$ (see note)
Signal level field strength at the EUT	72 dBμA/m	72 dBμA/m	82 dBμA/m

NOTE: F = OFR see clause 4.3.3.

10.3. Test Setup




Figure 11: Schematic test set-up for the RX-blocking test




Figure 12: Schematic test set-up for the RX-blocking test

10.4. Test Procedure

- a) The fulfilment of the WPT system performance criterion in all possible operational modes (see clause 4.2.3) shall be tested in presence of the inference signals according to Table 6.
- b) The manufacturer shall declare in which device orientation(s) (worst case) the test shall be performed.
- c) The WPT system shall initially operate without interference according to its specified sensitivity (detecting an specific object in the maximum depth as declared by the manufacturer (see clause 4.2.2 on wanted performance criteria)).
- d) The test setup is visualized in the following Figures 11 and 12.
- e) The tool shall be operated as intended (e.g. some tools might require to be moved across the object, some tool can be used stationary).
- f) The test shall be carried out inside a test chamber according to clauses C.1.1 and C.1.2 in ETSI EN 300 330 [1].
- g) A test loop with a radius r shall be used to create the magnetic field; the test loop shall lie on a non-metallic ground and the minimum distance to metallic objects (e.g. ground plane) shall be 0,75 m.
- h) The EUT shall be placed to the centre of the test-loop (e.g. see Figures 11 and 12).
- i) The test loop shall be sufficiently large so that the test loop itself does not influence the WPT system; The radius R of the test-loop shall be in minimum $\Delta R = 0,75$ m larger than the maximum dimension r of the EUT.
- j) (See Figure 12): $R \geq r + \Delta R$.
- k) The maximum H-Field can be calculated from the loop current I (into the test-loop) with the following formula:
- l) The required output current to achieve the required magnetic field from Table 12 at the WPT system shall be generated with a signal generator (unmodulated signal) at the test frequencies from Table 6.
- m) For each test frequency the "reaction" of the device shall be recorded and checked against the performance criterion from clause 4.2.2.
- n)

10.5. Test Result

PASS.

EUT Operational Mode	Interference			Conclusion
	Unwanted Input Signal Type	Test Frequency (KHz)	Unwanted Input Signal Level (dB μ A/m)	
Mode 3 (worst case)	In-band signal	$f_c = 165.0$ KHz	71	PASS
	OOB signal	$f_c - \text{OFR}$	71	PASS
		$f_c + \text{OFR}$	71	PASS
	Remote-band signal	$f_c - 10 \cdot \text{OFR}$	80	PASS
		$f_c + 10 \cdot \text{OFR}$	80	PASS

Note: $F = \text{OFR}$



11. LIST OF MEASURING EQUIPMENT



Manufacturer	Description	Model	Serial Number	Cal. Date	Due Date
SIDT FRANKONIA	3m Semi Anechoic Chamber	SAC-3M	03CH03-HY	2017/06/18	2018/06/17
EMI Test Receiver	ROHDE & SCHWARZ	ESCI	101142	2017/06/18	2018/06/17
Agilent	Spectrum Analyzer	E4407B	MY41440292	2017/06/16	2018/06/15
Agilent	MXA Signal Analyzer	N9020A	MY50510140	2017/10/27	2018/10/26
SCHWARZBECK	Loop Antenna	FMZB 1519	/	2017/11/01	2018/10/31
SCHWARZBECK	By-log Antenna	VULB9163	9163-470	2017/06/10	2018/06/09
EMCO	Horn Antenna	3115	6741	2017/06/10	2018/06/09
Jye Bao	RF Cable-R03m	RG142	CB021	2017/06/18	2018/06/17
SUHNER	RF Cable-HIGH	SUCOFLEX 106	03CH03-HY	2017/06/18	2018/06/17
B-Field Probe	Narda	ELT-400	M-1154	2018-04-11	2019-04-10



12.TEST SETUP PHOTOGRAPHS






13. EXTERIOR AND INTERIOR PHOTOGRAPHS OF EUT











-----THE END OF REPORT-----