

---

# RF Test Report

---

Report No.: AGC04094190401EE17

**PRODUCT DESIGNATION** : Bobby tech(wireless charger)  
**BRAND NAME** : N/A  
**MODEL NAME** : P705.251  
**CLIENT** : Xindao B.V.  
**DATE OF ISSUE** : Apr. 30, 2019  
**STANDARD(S)** : ETSI EN 303 417 V1.1.1(2017-09)  
**REPORT VERSION** : V1.0

**Attestation of Global Compliance (Shenzhen) Co., Ltd.**

**CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118

**Report Revise Record**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Apr. 30, 2019	Valid	Initial Release



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118

## TABLE OF CONTENTS

<b>1. TEST RESULT CERTIFICATION .....</b>	<b>4</b>
<b>2. EUT DESCRIPTION .....</b>	<b>5</b>
<b>3. DESCRIPTION OF TEST ITEMS .....</b>	<b>6</b>
<b>4. TEST FACILITY .....</b>	<b>6</b>
<b>5. ETSI EN 303 417 REQUIREMENT .....</b>	<b>7</b>
5.1 TRANSMITTER H-FIELD REQUIREMENTS .....	7
5.2 OPERATING FREQUENCY RANGES .....	12
5.3 TRANSMITTER OUT OF BAND (OOB) EMISSIONS .....	15
5.4 TRANSMITTER SPURIOUS EMISSIONS .....	18
5.5 RECEIVER BLOCKING .....	27
<b>6. INTERPRETATION OF MEASUREMENT RESULTS.....</b>	<b>29</b>
<b>APPENDIX 1: PHOTOGRAPHS OF TEST SETUP.....</b>	<b>30</b>



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118

## 1. TEST RESULT CERTIFICATION

<b>Applicant</b>	Xindao B.V.
<b>Address</b>	P.O. Box 3082, 2280 GB, Rijswijk, The Netherlands
<b>manufacturer</b>	Xindao B.V.
<b>Address</b>	P.O. Box 3082, 2280 GB, Rijswijk, The Netherlands
<b>Factory</b>	Xindao B.V.
<b>Address</b>	P.O. Box 3082, 2280 GB, Rijswijk, The Netherlands
<b>Product Designation</b>	Bobby tech(wireless charger)
<b>Brand Name</b>	N/A
<b>Test Model</b>	P705.251
<b>Date of test</b>	Apr. 17, 2019 to Apr. 28, 2019
<b>Deviation</b>	None
<b>Condition of Test Sample</b>	Normal
<b>Test Result</b>	Pass
<b>Report Template</b>	AGCRT-EC-RF

The above equipment was tested by SHENZHEN ATTESTATION OF GLOBAL COMPLIANCE (SHENZHEN) CO., LTD. for compliance with the requirements set forth in the European Standard ETSI EN 303 417 V1.1.1. The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By



Erik Yang(Yang Jianmin)

Apr. 28, 2019

Reviewed By



Max Zhang(Zhang Yi)

Apr. 30, 2019

Approved By



Forrest Lei(Lei Yonggang)  
Authorized Officer

Apr. 30, 2019



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118



## 2. EUT DESCRIPTION

Details of technical specification refer to the description in follows:

<b>Hardware Version</b>	CD-1054P_V1.3
<b>Software Version</b>	V1.0
<b>Operate Frequency</b>	Energy transmission: 100-205kHz Data communication:127.6KHz
<b>OCW</b>	0.832kHz
<b>Test Channels</b>	Energy transmission: Low channel 100KHz, High channel 205kHz Data communication:127.6KHz
<b>Antenna Type</b>	Integral antenna
<b>Operational Mode(See note)</b>	Mode 1: base station in stand-by, idle mode Mode 2: communication before charging, adjustment charging mode / position Mode 3: communication Mode 4: energy transmission
<b>Power Supply</b>	DC 5V 2A or DC 9V 1.67A by adaptor

**NOTE:** 1. For more information, please refer to User's Manual.

2. During the initial establishment of the charging mode (mode 2), no or very low emission occur (below the sensitivity level of the test set-up), so the mode 2 can be assumed as irrelevant for the test.

3. Mode 3 and mode 4 have been performed within one set-up, worst-case alignment. But each mode have been tested separately with specific test software.

4. The maximum temperature of 40 is not a standard requirement and is measured according to the maximum service temperature stated by the manufacturer.



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118

### 3. DESCRIPTION OF TEST ITEMS

Harmonised Standard ETSI EN 303 417		
Requirement		Requirement Conditionality
No	Description	
1	Permitted range of operating frequencies	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable
2	Operating frequency ranges	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable
3	H-field requirements	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable
4	Transmitter spurious emissions	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable
5	Transmitter out of band (OOB) emissions	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable
6	WPT system unwanted conducted emissions	<input type="checkbox"/> Applicable <input checked="" type="checkbox"/> Not Applicable
7	Receiver blocking	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable

### 4. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118


## 5. ETSI EN 303 417 REQUIREMENT

### 5.1 TRANSMITTER H-FIELD REQUIREMENTS

#### MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	100096	Jun. 12, 2018	Jun. 11, 2019
Amplifier	EM	EM30180	060552	Jun. 12, 2018	Jun. 11, 2019
LOOP ANTENNA	A.H.	SAS-526B	--	Mar. 01, 2018	Feb. 28, 2020

#### TEST SETUP:



# TEST LIMITS:

The H-field limit in dB $\mu$ A/m at 3 m,  $H_{3m}$ , is determined by the following equation:

$$H_{3m} = H_{10m} + C_3 \text{ (F.2)}$$

Where:  $H_{10m}$  is the H-field limit in dB $\mu$ A/m at 10 m distance according to the present document; and  $C_3$  is a conversion factor in dB determined from figure F.2.

According to EN 303 417 Tablet 3,

Table 3: H-field limits

Frequency range [MHz]	H-field strength limit [dB $\mu$ A/m at 10 m]	Comments
$0,019 \leq f < 0,021$	72	
$0,059 \leq f < 0,061$	69,1 descending 10 dB/dec above 0,059 MHz	See note 1
$0,079 \leq f < 0,090$	67,8 descending 10 dB/dec above 0,079 MHz	See note 2
$0,100 \leq f < 0,119$	42	
$0,119 \leq f < 0,135$	66 descending 10 dB/dec above 0,119 MHz	See note 1
$0,135 \leq f < 0,140$	42	
$0,140 \leq f < 0,1485$	37,7	
$0,1485 \leq f < 0,30$	-5	
$6,765 \leq f < 6,795$	42	

NOTE 1: Limit is 42 dB $\mu$ A/m for the following spot frequencies: 60 kHz  $\pm$  250 Hz and 129,1 kHz  $\pm$  500 Hz.  
NOTE 2: At the time of preparation of the present document the feasibility of increased limits for high power wireless power transmission systems to charge vehicles [1.4] was prepared. New specific requirements for such systems (e.g. higher H-field emission limits in the 79 - 90 kHz band) will be reflected within a future revision of the present document.

The limit at 10 m( $H_{10m}$ ) is= 65.7dB $\mu$ A/m.

Owing to the frequency EUT is 127.6kHz, so the  $C_3$  approach to 31.2dB.

So the  $H_{3m}$  = 96.9dB $\mu$ A/m.

Correction factor,  $C_3$ , for limits at 3 m distance, dB




Figure F.2: Conversion factor  $C_3$  versus frequency



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118



### TEST PROCEDURE:

The EUT was placed on the top of an insulating table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

The H-field is measured with a shielded loop antenna connected to a measurement receiver.

The measuring bandwidth and detector type of the measurement receiver shall be in accordance with EN 300 330 V2.1.1 Table 11.

The EUT operate with modulation under normal and extreme conditions.

### TEST RESULTS:

Test Mode: Mode 1

Extreme conditions state

conditions	Test Temp	Test Volt.(V)	Note
TN/VN	25°C	9.0	Worst case
TL/ VL	-10°C	8.1	
TH/ML	40°C	8.1	
TL/VH	-10°C	9.0	
TH/VH	40°C	9.0	

Test results tested at 3m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1276	23.54	-3.72	19.82	96.9

Test results calculated to 10m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1276	23.54	-34.92	-11.38	65.7



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118

Test Mode: Mode 3

Extreme conditions state

conditions	Test Temp	Test Volt.(V)	Note
TN/VN	25°C	9.0	Worst case
TL/ VL	-10°C	8.1	
TH/VL	40°C	8.1	
TL/VH	-10°C	9.0	
TH/VH	40°C	9.0	

Test results tested at 3m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1276	23.54	-3.58	19.96	96.9

Test results calculated to 10m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1276	23.54	-34.78	-11.24	65.7



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118

Test Mode: Mode 4

Extreme conditions state

conditions	Test Temp	Test Volt.(V)	Note
TN/VN	25°C	9.0	Worst case
TL/ VL	-10°C	8.1	
TH/VL	40°C	8.1	
TL/VH	-10°C	9.0	
TH/VH	40°C	9.0	

Test results tested at 3m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1065	23.54	-1.13	22.41	73.20
0.1470	23.54	-3.42	20.12	68.9
0.2050	23.54	-4.13	19.41	26.20

Test results calculated to 10m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1065	23.54	-32.33	-8.79	42.00
0.1470	23.54	-34.62	-11.08	37.7
0.2050	23.54	-35.33	-11.79	-5.00



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com


Service Hotline:400 089 2118

## 5.2 OPERATING FREQUENCY RANGES

### MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	100096	Jun. 12, 2018	Jun. 11, 2019
Amplifier	EM	EM30180	060552	Jun. 12, 2018	Jun. 11, 2019
LOOP ANTENNA	A.H.	SAS-526B	--	Mar. 01, 2018	Feb. 28, 2020

### TEST SETUP:



### TEST PROCEDURE:

- 1). The EUT was placed on a turn table which is 0.8m above ground plane.
- 2). The EUT was modulated by normal signal,
- 3). Set SPA Center Frequency = fundamental frequency, RBW=VBW=200Hz, Span=5kHz, Detector=RMS. The 99 % OBW function shall be used to determine the operating frequency range, fH is the frequency of the upper marker resulting from the OFR, fL is the frequency of the lower marker resulting from the OFR.
- 4). Both normal test condition and extreme test condition applied

### LIMITS

The operating frequency range for emissions shall be within one of the following limits: 19 - 21 kHz, 59 - 61 kHz, 79 - 90 kHz, 100 - 300 kHz, 6 765 - 6 795 kHz.



## TEST RESULT

Test Mode: Mode 3

### Frequency Range Test Result

Test Temperature	Test Voltage (V DC)	Lowest Frequency (fL)	Highest Frequency (fH)	Limit
-10℃	8.1	127.186KHz	128.018KHz	100kHz≤&≤300kHz
	9.0	127.183KHz	128.015KHz	100kHz≤&≤300kHz
25℃	9.0	127.184KHz	128.016KHz	100kHz≤&≤300kHz
40℃	8.1	127.181KHz	128.013KHz	100kHz≤&≤300kHz
	9.0	127.185KHz	128.017KHz	100kHz≤&≤300kHz
OFR		0.832kHz		
Results		PASS		

Test Mode: Mode 1

### Frequency Range Test Result

Test Temperature	Test Voltage (V DC)	Lowest Frequency (fL)	Highest Frequency (fH)	Limit
-10℃	8.1	127.232KHz	127.95 KHz	100kHz≤&≤300kHz
	9.0	127.234KHz	127.958KHz	100kHz≤&≤300kHz
25℃	9.0	127.238KHz	127.962KHz	100kHz≤&≤300kHz
40℃	8.1	127.235KHz	127.959KHz	100kHz≤&≤300kHz
	9.0	127.237KHz	127.961KHz	100kHz≤&≤300kHz
OFR		0.724kHz		
Results		PASS		



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118

Test Mode: Mode 4

## Frequency Range Test Result

Test Temperature	Test Voltage (V DC)	Lowest Frequency (fL)	Highest Frequency (fH)	Limit
-10℃	8.0	106.088kHz	205.360kHz	100kHz≤&≤300kHz
	9.0	106.086kHz	205.358kHz	100kHz≤&≤300kHz
25℃	9.0	106.081kHz	205.361kHz	100kHz≤&≤300kHz
40℃	8.1	106.083kHz	205.362kHz	100kHz≤&≤300kHz
	9.0	106.084kHz	205.356 kHz	100kHz≤&≤300kHz
OFR		99.280kHz		
Results		PASS		

**NOTE:** All the modes had been tested, but only the worst data recorded in the report.



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China


Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Service Hotline:400 089 2118

### 5.3 TRANSMITTER OUT OF BAND (OOB) EMISSIONS

#### MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	100096	Jun. 12, 2018	Jun. 11, 2019
Amplifier	EM	EM30180	060552	Jun. 12, 2018	Jun. 11, 2019
LOOP ANTENNA	A.H.	SAS-526B	--	Mar. 01, 2018	Feb. 28, 2020

#### TEST SETUP:



#### TEST PROCEDURE:

- 1). The EUT was placed on a turn table which is 0.8m above ground plane.
- 2). The EUT was modulated by normal signal,
- 3). Set SPA Center Frequency = fundamental frequency, RBW=VBW=200Hz, Span=5KHz, Detector=RMS. The 99 % OBW function shall be used to determine the operating frequency range, fH is the frequency of the upper marker resulting from the OFR, fL is the frequency of the lower marker resulting from the OFR.
- 4). Both normal test condition and extreme test condition applied

## LIMITS

The OOB limits are visualized in figures; they are descending from the intentional limits from Table 3 at  $f_H/f_L$  with 10 dB/decade.




Figure 4: Out of band and spurious domain of a single frequency WPT system

## TEST RESULT

Test Mode: Mode 3

Frequency range (KHz)		Maximum level @10m (dBuA/m)	Limit @ 10m (dBuA/m)	Result
fSL -fL	125.520 to 127.184	Less than -18.14	See figure 4	Pass
fL	127.184	-18.14	65.7	Pass
fH	128.016	-18.08	65.7	Pass
fH - fSH	128.016 to 129.68	Less than -18.08	See figure 4	Pass

Test Mode: Mode 1

Frequency range (KHz)		Maximum level @10m (dBuA/m)	Limit @ 10m (dBuA/m)	Result
fSL -fL	125.790 to 127.238	Less than -18.47	See figure 4	Pass
fL	127.238	-18.47	65.7	Pass
fH	127.962	-18.35	65.7	Pass
fH - fSH	127.962 to 129.41	Less than -18.35	See figure 4	Pass



Attestation of Global Compliance (Shenzhen) Co., Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118



Test Mode: Mode 4

Frequency range (KHz)		Maximum level @10m (dBuA/m)	Limit @ 10m (dBuA/m)	Result
fSL -fL	104.440 to 106.081	Less than -17.56	See figure 4	Pass
fL	106.081	-17.56	42	Pass
fH	205.361	-16.23	-5	Pass
fH - fSH	205.361 to 206.800	Less than -16.23	See figure 4	Pass

**NOTE:** All the modes had been tested, but only the worst data recorded in the report.



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118


## 5.4 TRANSMITTER SPURIOUS EMISSIONS

### MEASUREMENT EQUIPMENT USED:


NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	100096	Jun. 12, 2018	Jun. 11, 2019
Amplifier	EM	EM30180	060552	Jun. 12, 2018	Jun. 11, 2019
LOOP ANTENNA	A.H.	SAS-526B	--	Mar. 01, 2018	Feb. 28, 2020
ANTENNA	SCHWARZBECK	VULB9168	494	Mar. 01, 2018	Feb. 28, 2020

### TEST SETUP:

#### FREQUENCY RANGE (9KHZ-30MHZ)



#### FREQUENCY RANGE (ABOVE 30MHZ)



Attestation of Global Compliance (Shenzhen) Co., Ltd.


Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

# **SUBSTITUTION METHOD:** **RADIATED BELOW 1GHZ**



## **TEST PROCEDURE:**

For test method of frequency range (9 kHz-30MHz)

The EUT was placed on the top of an insulating table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

The H-field is measured with a shielded loop antenna connected to a measurement receiver.

The measuring bandwidth and detector type of the measurement receiver shall be in accordance with EN 300 330 Table 1.

For test method of frequency range (30 MHz-1000MHz)

EUT was placed on a 1.5m height wooden table. The search antenna is placed at 3m distances from the EUT and search antenna height is from 1-4m. With the transmitter operating at continuously mode, the turntable was slowly rotated to locate the direction of maximum emission. Once maximum direction is determined, the search antenna was raised and lowered in both vertical and horizontal polarizations.

The EUT was removed from the turntable and replaced with a linearly polarized antenna connected to a calibrated RF signal generator. The RF generator was set to a measured emission frequency and the search antenna was raised and lowered to produce a maximum received reading. The generator output was increased to match the radiated emission reading measured previously, and the result expressed in dB EIRP or ERP, correcting for substitution antenna gain at each frequency.

## LIMITS OF RADIATED DISTURBANCES

Below 30MHz

**Table 4**

State (see note)	Frequency $9 \text{ kHz} \leq f < 10 \text{ MHz}$	Frequency $10 \text{ MHz} \leq f < 30 \text{ MHz}$
Operating	27 dB $\mu$ A/m at 9 kHz descending 10 dB/dec	-3,5 dB $\mu$ A/m
Standby	5,5 dB $\mu$ A/m at 9 kHz descending 10 dB/dec	-25 dB $\mu$ A/m
NOTE: "Operating" means mode 2, 3 and 4 according to Table 2; "standby" means mode 1 according to Table 2.		

**Table 5**

State (see note)	47 MHz to 74 MHz 87,5 MHz to 118 MHz 174 MHz to 230 MHz 470 MHz to 790 MHz	Other frequencies between 30 MHz to 1 000 MHz
Operating	4 nW	250 nW
Standby	2 nW	2 nW
NOTE: "Operating" means mode 2, 3 and 4 according to Table 2; "standby" means mode 1 according to Table 2.		



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118



## TEST LIMITS & RESULT

Test Mode: Mode 3  
FREQUENCY RANGE (9KHZ-30MHZ)

Operation Mode					
Frequency	Reading level	Total Factor	Emission level	Limit	Margin
(MHz)	(dB $\mu$ A)	(dB/m )	(dB $\mu$ A/m)	(dB $\mu$ A/m)	(dB $\mu$ A/m)
0.042	-6.91	-7.96	-14.87	20.31	35.18
0.245	-10.97	-7.96	-18.93	12.65	31.58
0.421	-12.25	-7.96	-20.21	10.30	30.51
1.54	-10.95	-3.98	-14.93	4.67	19.60
2.755	-13.19	-3.09	-16.28	2.14	18.42
3.818	-14.06	-1.25	-15.31	0.72	16.03

Remark:

- (1) Corrected Power (dBm) = Total Factor + Reading Level
- (2) Measuring frequencies from 9KHz to the 30MHz.
- (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Service Hotline:400 089 2118

## FREQUENCY RANGE (ABOVE 30MHZ)

Transmitter Spurious Emission below 1GHz (30MHz-1GHz)

Frequency	Reading Level	Antenna	S.G.	Cable Loss	Ant.Gain	Emission Level	Limit	Margin
(MHz)	(dBuv/m)	Polarization	(dBm)	(dB)	(dBi)	(dBm)	(dBm)	(dB)
84.50	30.56	V	-60.37	0.48	0.54	-60.31	-36.00	24.31
129.78	31.18	V	-59.73	0.49	0.14	-60.08	-36.00	24.08
239.92	30.85	V	-66.91	0.52	6.60	-60.83	-36.00	24.83
326.08	30.53	V	-66.37	0.53	6.10	-60.80	-36.00	24.80
334.39	30.84	V	-64.42	0.53	5.94	-59.01	-36.00	23.01
827.13	31.76	V	-64.00	0.66	6.45	-58.21	-54.00	4.21
83.94	31.66	H	-59.53	0.48	0.38	-59.63	-36.00	23.63
131.65	30.16	H	-62.56	0.49	0.08	-62.97	-36.00	26.97
242.65	29.84	H	-68.89	0.52	6.72	-62.69	-36.00	26.69
326.00	30.38	H	-66.43	0.53	6.10	-60.86	-36.00	24.86
735.49	30.70	H	-64.97	0.59	6.60	-58.97	-54.00	4.97
828.28	31.05	H	-64.21	0.66	6.40	-58.47	-54.00	4.47

Note: 1. The margins of the other spectrum are not exceeding the minimum value of margin, and this part of the results without recording in the test report.

2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "--" remark, if no specific emission from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118

**Test Mode: Mode 4(The low channel is the worst case)**  
**FREQUENCY RANGE (9KHZ-30MHZ)**

Operation Mode					
Frequency	Reading level	Total Factor	Emission level	Limit	Margin
(MHz)	(dB $\mu$ A)	(dB/m )	(dB $\mu$ A/m)	(dB $\mu$ A/m)	(dB $\mu$ A/m)
0.04	-6.92	-7.96	-14.88	20.52	35.40
0.243	-10.99	-7.96	-18.95	12.69	31.64
0.42	-12.27	-7.96	-20.23	10.31	30.54
1.538	-10.97	-3.98	-14.95	4.67	19.62
2.753	-13.21	-3.09	-16.3	2.14	18.44
3.815	-14.08	-1.25	-15.33	0.73	16.06

**Remark:**

(1) Corrected Power (dBm) = Total Factor + Reading Level

(2) Measuring frequencies from 9KHz to the 30MHz.

(3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118

## FREQUENCY RANGE (ABOVE 30MHZ)

Transmitter Spurious Emission below 1GHz (30MHz-1GHz)

Frequency	Reading Level	Antenna	S.G.	Cable Loss	Ant.Gain	Emission Level	Limit	Margin
(MHz)	(dBuv/m)	Polarization	(dBm)	(dB)	(dBi)	(dBm)	(dBm)	(dB)
84.83	30.64	V	-60.71	0.48	0.54	-60.65	-36.00	24.65
129.80	30.77	V	-61.16	0.49	0.14	-61.51	-36.00	25.51
240.33	31.23	V	-67.49	0.52	6.60	-61.41	-36.00	25.41
326.49	30.27	V	-67.42	0.53	6.10	-61.85	-36.00	25.85
334.38	31.54	V	-64.10	0.53	5.94	-58.69	-36.00	22.69
827.44	32.20	V	-66.28	0.66	6.45	-60.49	-54.00	6.49
84.21	31.62	H	-57.67	0.48	0.54	-57.61	-36.00	21.61
131.47	31.10	H	-59.29	0.49	0.08	-59.70	-36.00	23.70
243.22	29.92	H	-65.84	0.52	6.78	-59.58	-36.00	23.58
325.71	30.85	H	-64.73	0.53	6.10	-59.16	-36.00	23.16
735.40	30.72	H	-65.25	0.59	6.60	-59.24	-54.00	5.24
827.96	31.15	H	-64.61	0.66	6.45	-58.82	-54.00	4.82

Note: 1. The margins of the other spectrum are not exceeding the minimum value of margin, and this part of the results without recording in the test report.

2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "--" remark, if no specific emission from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Service Hotline:400 089 2118



**Test Mode: Mode 1**  
**FREQUENCY RANGE (9KHZ-30MHZ)**

Standby Mode					
Frequency	Reading level	Total Factor	Emission level	Limit	Margin
(MHz)	(dB $\mu$ A)	(dB/m )	(dB $\mu$ A/m)	(dB $\mu$ A/m)	(dB $\mu$ A/m)
0.032	-8.72	-7.96	-16.68	-0.01	16.67
0.241	-11.65	-7.96	-19.61	-8.78	10.83
0.405	-13.46	-7.96	-21.42	-11.03	10.39
1.5281	-22.53	-3.98	-26.51	-16.80	9.71
2.736	-24.37	-3.09	-27.46	-19.33	8.13
3.823	-24.43	-1.25	-25.68	-20.78	4.90

**Remark:**

- (1) Corrected Power (dBm) = Total Factor + Reading Level
- (2) Measuring frequencies from 9KHz to the 30MHz.
- (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118

# FREQUENCY RANGE (ABOVE 30MHZ)

Transmitter Spurious Emission below 1GHz (30MHz-1GHz)

Frequency	Reading Level	Antenna	S.G.	Cable Loss	Ant.Gain	Emission Level	Limit	Margin
(MHz)	(dBuv/m)	Polarization	(dBm)	(dB)	(dBi)	(dBm)	(dBm)	(dB)
114.42	30.92	V	-71.84	0.48	1.40	-70.92	-57.00	13.92
177.02	32.21	V	-73.73	0.51	3.06	-71.18	-57.00	14.18
229.62	29.48	V	-77.20	0.52	6.84	-70.88	-57.00	13.88
495.89	30.14	V	-77.15	0.56	7.05	-70.66	-57.00	13.66
664.54	30.85	V	-76.85	0.59	6.98	-70.46	-57.00	13.46
880.38	30.34	V	-75.73	0.69	5.90	-70.52	-57.00	13.52
84.22	32.34	H	-70.78	0.48	0.54	-70.72	-57.00	13.72
109.78	30.97	H	-71.92	0.48	1.28	-71.12	-57.00	14.12
219.47	31.04	H	-77.84	0.52	7.38	-70.98	-57.00	13.98
485.45	31.25	H	-77.54	0.56	7.00	-71.10	-57.00	14.10
554.98	30.48	H	-80.16	0.57	6.78	-73.95	-57.00	16.95
635.17	31.41	H	-78.42	0.58	7.20	-71.80	-57.00	14.80

Note: 1.The margins of the other spectrum are not exceeding the minimum value of margin, and this part of the results without recording in the test report.

2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "--" remark, if no specific emission from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China


Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Service Hotline:400 089 2118

## 5.5 RECEIVER BLOCKING

### MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
MXG X-Series Vector Signal Generator	Agilent	N5182B	N/A	Sep. 20, 2018	Sep. 19, 2019
LOOP ANTENNA	LAPLACE	RF300	N/A	Mar. 01, 2018	Feb. 28, 2020
Clamp meter	PROVA	PROVA-11	17200101	Sep. 20, 2018	Sep. 19, 2019

### TEST SETUP:



### TEST PROCEDURE:

- 1). The test shall be carried out inside a test chamber according to clauses C.1.1 and C.1.2 in ETSI EN 300 330
- 2). A test loop with a radius  $r$  shall be used to create the magnetic field; the test loop shall lie on a non-metallic ground and the minimum distance to metallic objects (e.g. ground plane) shall be 0,75 m. The EUT shall be placed to the centre of the test-loop
- 3). The test loop shall be sufficiently large so that the test loop itself does not influence the WPT system; The radius  $R$  of the test-loop shall be in minimum  $\Delta R = 0,75$  m larger than the maximum dimension  $r$  of the EUT.

$$R \geq r + \Delta R.$$

The maximum H-Field can be calculated from the loop current  $I$  (into the test-loop) with the following formula:

$$H = I/2R$$



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118

4) The required output current to achieve the required magnetic field at the WPT system shall be generated with a signal generator (unmodulated signal) at the test frequencies. For each test frequency the "reaction" of the device shall be recorded and checked against the performance criterion

## LIMITS

The EUT shall achieve the wanted performance criterion, in the presence of the blocking signal.

**Table 6: Receiver blocking limits**

	In-band signal	OOB signal	Remote-band signal
Frequency	Centre frequency ( $f_c$ ) of the WPT system (see clause 4.3.3)	$f = f_c \pm F$ (see note)	$f = f_c \pm 10 \times F$ (see note)
Signal level field strength at the EUT	72 dB $\mu$ A/m	72 dB $\mu$ A/m	82 dB $\mu$ A/m
NOTE: F = OFR see clause 4.3.3.			

## TEST RESULT

Test Mode: Mode 3

Test Frequency(KHz)		Signal level @ EUT	Performance	Result
In-band signal	127.600	72dBuA/m	No function loss	Pass
OOB signal	126.768	72dBuA/m	No function loss	Pass
	128.432	72dBuA/m	No function loss	Pass
Remote-band signal	119.280	82dBuA/m	No function loss	Pass
	135.920	82dBuA/m	No function loss	Pass

Test Mode: Mode 1

Test Frequency(KHz)		Signal level @ EUT	Performance	Result
In-band signal	127.600	72dBuA/m	No function loss	Pass
OOB signal	126.876	72dBuA/m	No function loss	Pass
	128.324	72dBuA/m	No function loss	Pass
Remote-band signal	120.360	82dBuA/m	No function loss	Pass
	134.840	82dBuA/m	No function loss	Pass



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118



## 6. INTERPRETATION OF MEASUREMENT RESULTS

All the measurement equipments and accessories have been carefully selected to meet the maximum measurement uncertainty specified below:

RF Frequency	$\pm 1 \times 10^{-7}$
RF Power, Conducted	$\pm 0.75\text{dB}$
Maximum Frequency Deviation: _ Within 300Hz and 6KHz of Audio Frequency _ Within 6KHz and 25KHz of Audio Frequency	$\pm 5\%$ $\pm 3\text{dB}$
Adjacent channel power	$\pm 3\text{dB}$
Conducted Emission of Transmitter, Valid Up to 12.75GHz	$\pm 4\text{dB}$
Conducted Emissions of Receivers	$\pm 3\text{dB}$
Radiated Emission of Transmitter, Valid Up to 12.75GHz	$\pm 6\text{dB}$

P.S. Uncertainty figures are valid to confidence level of 95% calculated according to the methods described in the ETSI TR 100 028.



Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118

## APPENDIX 1: PHOTOGRAPHS OF TEST SETUP



----END OF REPORT----



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,  
Xixiang, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118