
RF Test Report

Report No.: AGC04094190911EE17

PRODUCT DESIGNATION : 15W Wireless Fast Charger

BRAND NAME : N/A

MODEL NAME : P308.31

APPLICANT : Xindao B.V.

DATE OF ISSUE : Nov. 28, 2019

STANDARD(S) : ETSI EN 303 417 V1.1.1(2017-09)

REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd.

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Nov. 28, 2019	Valid	Initial Release



TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION	4
2. EUT DESCRIPTION	5
3. DESCRIPTION OF TEST ITEMS	6
4. TEST FACILITY	6
5. ETSI EN 303 417 REQUIREMENT	7
5.1 TRANSMITTER H-FIELD REQUIREMENTS	7
5.2 OPERATING FREQUENCY RANGES	12
5.3 TRANSMITTER OUT OF BAND (OOB) EMISSIONS	15
5.4 TRANSMITTER SPURIOUS EMISSIONS.....	18
5.5 RECEIVER BLOCKING	27
6. INTERPRETATION OF MEASUREMENT RESULTS.....	29
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	30
APPENDIX B: PHOTOGRAPHS OF THE EUT	31



1. TEST RESULT CERTIFICATION

Applicant	Xindao B.V.
Address	P.O. Box 3082, 2280 GB, Rijswijk, The Netherlands
Manufacturer	Xindao B.V.
Address	P.O. Box 3082, 2280 GB, Rijswijk, The Netherlands
Factory	Xindao B.V.
Address	P.O. Box 3082, 2280 GB, Rijswijk, The Netherlands
Product Designation	15W Wireless Fast Charger
Brand Name	N/A
Test Model	P308.31
Date of test	Sep. 11, 2019 to Nov. 27, 2019
Deviation	None
Condition of Test Sample	Normal
Test Result	Pass
Report Template	AGCRT-EC-RF

The above equipment was tested by SHENZHEN ATTESTATION OF GLOBAL COMPLIANCE (SHENZHEN) CO., LTD. for compliance with the requirements set forth in the European Standard ETSI EN 303 417 V1.1.1. The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.


Prepared By



Donjon Huang
(Project Engineer)

Nov. 27, 2019

Reviewed By



Max Zhang
(Reviewer)

Nov. 28, 2019

Approved By



Forrest Lei
(Authorized Officer)

Nov. 28, 2019

2. EUT DESCRIPTION

Details of technical specification refer to the description in follows:

Hardware Version	LWK-F10-15W-EMI
Software Version	V1.0
Operate Frequency	Energy transmission: 110-205kHz Data communication:175.7KHz
OCW	0.534kHz
Test Channels	Energy transmission: Low channel 110KHz, High channel 205kHz Data communication:175.7KHz
Antenna Type	Integral antenna
Operational Mode(See note)	Mode 1: base station in stand-by, idle mode Mode 2: communication before charging, adjustment charging mode / position Mode 3: communication Mode 4: energy transmission
Power Supply	DC 5V 2A or DC 9V 2A by adapter

NOTE: 1. For more information, please refer to User's Manual.

2. During the initial establishment of the charging mode (mode 2), no or very low emission occur (below the sensitivity level of the test set-up), so the mode 2 can be assumed as irrelevant for the test.

3. Mode 3 and mode 4 have been performed within one set-up, worst-case alignment. But each mode have been tested separately with specific test software.

4. The minimum/maximum temperature of -10/40°C is not a standard requirement and is measured according to the maximum service temperature stated by the manufacturer.



3. DESCRIPTION OF TEST ITEMS

Harmonised Standard ETSI EN 303 417		
Requirement		Requirement Conditionality
No	Description	
1	Permitted range of operating frequencies	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable
2	Operating frequency ranges	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable
3	H-field requirements	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable
4	Transmitter spurious emissions	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable
5	Transmitter out of band (OOB) emissions	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable
6	WPT system unwanted conducted emissions	<input type="checkbox"/> Applicable <input checked="" type="checkbox"/> Not Applicable
7	Receiver blocking	<input checked="" type="checkbox"/> Applicable <input type="checkbox"/> Not Applicable

4. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China


5. ETSI EN 303 417 REQUIREMENT

5.1 TRANSMITTER H-FIELD REQUIREMENTS

MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Jun. 12, 2019	Jun. 11, 2020
Amplifier	ETS-LINDGREN	3117PA	00225134	Oct. 15, 2019	Oct. 14, 2020
LOOP ANTENNA	LAPLACE	RF300	--	Feb. 19, 2019	Feb. 18, 2021

TEST SETUP:



TEST LIMITS:

The H-field limit in dBμA/m at 3 m, H_{3m} , is determined by the following equation:

$$H_{3m} = H_{10m} + C_3 \text{ (F.2)}$$

Where: H_{10m} is the H-field limit in dBμA/m at 10 m distance according to the present document; and C_3 is a conversion factor in dB determined from figure F.2.

According to EN 303 417 Tablet 3,

Table 3: H-field limits

Frequency range [MHz]	H-field strength limit [dBμA/m at 10 m]	Comments
$0,019 \leq f < 0,021$	72	
$0,059 \leq f < 0,061$	69,1 descending 10 dB/dec above 0,059 MHz	See note 1
$0,079 \leq f < 0,090$	67,8 descending 10 dB/dec above 0,079 MHz	See note 2
$0,100 \leq f < 0,119$	42	
$0,119 \leq f < 0,135$	66 descending 10 dB/dec above 0,119 MHz	See note 1
$0,135 \leq f < 0,140$	42	
$0,140 \leq f < 0,1485$	37,7	
$0,1485 \leq f < 0,30$	-5	
$6,765 \leq f < 6,795$	42	

NOTE 1: Limit is 42 dBμA/m for the following spot frequencies: 60 kHz ± 250 Hz and 129,1 kHz ± 500 Hz.
NOTE 2: At the time of preparation of the present document the feasibility of increased limits for high power wireless power transmission systems to charge vehicles [1.4] was prepared. New specific requirements for such systems (e.g. higher H-field emission limits in the 79 - 90 kHz band) will be reflected within a future revision of the present document.

The limit at 10 m (H_{10m}) is -5.0 dBμA/m.

Owing to the frequency EUT is 175.7 kHz, so the C_3 approach to 31.2 dB.

So the $H_{3m} = 26.2$ dBμA/m.

Correction factor, C_3 , for limits at 3 m distance, dB




Figure F.2: Conversion factor C_3 versus frequency

TEST PROCEDURE:

The EUT was placed on the top of an insulating table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

The H-field is measured with a shielded loop antenna connected to a measurement receiver.

The measuring bandwidth and detector type of the measurement receiver shall be in accordance with EN 300 330 V2.1.1 Table 11.

The EUT operate with modulation under normal and extreme conditions.

TEST RESULTS:

Test Mode: Mode 1

Extreme conditions state

conditions	Test Temp	Test Volt.(V)	Note
TN/VN	25°C	9.0	Worst case
TL/ VL	-10°C	8.1	
TH/ML	40°C	8.1	
TL/VH	-10°C	9.0	
TH/VH	40°C	9.0	

Test results tested at 3m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1757	23.53	-2.41	21.12	26.20

Test results calculated to 10m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1757	23.53	-33.61	-10.08	-5.00

Test Mode: Mode 3

Extreme conditions state

conditions	Test Temp	Test Volt.(V)	Note
TN/VN	25°C	9.0	Worst case
TL/ VL	-10°C	8.1	
TH/VL	40°C	8.1	
TL/VH	-10°C	9.0	
TH/VH	40°C	9.0	

Test results tested at 3m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1757	23.53	-3.26	20.27	26.20

Test results calculated to 10m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1757	23.53	-34.46	-10.93	-5.00



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

Test Mode: Mode 4

Extreme conditions state

conditions	Test Temp	Test Volt.(V)	Note
TN/VN	25°C	9.0	Worst case
TL/ VL	-10°C	8.1	
TH/VL	40°C	8.1	
TL/VH	-10°C	9.0	
TH/VH	40°C	9.0	

Test results tested at 3m test sites:

Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1159	23.53	-2.24	21.29	73.20
0.1468	23.53	-3.54	19.99	68.90
0.1757	23.53	-5.04	18.49	26.20

Test results calculated to 10m test sites:


Freq.	Antenna Factor	Reading Level	Corrected Level	Limit
(MHz)	(dB/m)	(dBuA)	(dBuA/m)	(dBuA/m)
0.1159	23.53	-33.44	-9.91	42.00
0.1468	23.53	-34.74	-11.21	37.70
0.1757	23.53	-36.24	-12.71	-5.00

5.2 OPERATING FREQUENCY RANGES

MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Jun. 12, 2019	Jun. 11, 2020
Amplifier	ETS-LINDGREN	3117PA	00225134	Oct. 15, 2019	Oct. 14, 2020
LOOP ANTENNA	LAPLACE	RF300	--	Feb. 19, 2019	Feb. 18, 2021

TEST SETUP:



TEST PROCEDURE:

- 1). The EUT was placed on a turn table which is 0.8m above ground plane.
- 2). The EUT was modulated by normal signal,
- 3). Set SPA Center Frequency = fundamental frequency, RBW=VBW=200Hz, Span=5kHz, Detector=RMS. The 99 % OBW function shall be used to determine the operating frequency range, fH is the frequency of the upper marker resulting from the OFR, fL is the frequency of the lower marker resulting from the OFR.
- 4). Both normal test condition and extreme test condition applied

LIMITS

The operating frequency range for emissions shall be within one of the following limits: 19 - 21 kHz, 59 - 61 kHz, 79 - 90 kHz, 100 - 300 kHz, 6 765 - 6 795 kHz.

TEST RESULT

Test Mode: Mode 3

Frequency Range Test Result

Test Temperature	Test Voltage (V DC)	Lowest Frequency (fL)	Highest Frequency (fH)	Limit
-10℃	8.1	175.434 kHz	175.962 kHz	100kHz≤&≤300kHz
	9.0	175.437 kHz	175.962 kHz	100kHz≤&≤300kHz
25℃	9.0	175.433 kHz	175.967 kHz	100kHz≤&≤300kHz
40℃	8.1	175.433 kHz	175.967 kHz	100kHz≤&≤300kHz
	9.0	175.436 kHz	175.964 kHz	100kHz≤&≤300kHz
OFR		0.534kHz		
Results		PASS		

Test Mode: Mode 1

Frequency Range Test Result

Test Temperature	Test Voltage (V DC)	Lowest Frequency (fL)	Highest Frequency (fH)	Limit
-10℃	8.1	175.465 kHz	175.936 kHz	100kHz≤&≤300kHz
	9.0	175.465 kHz	175.935 kHz	100kHz≤&≤300kHz
25℃	9.0	175.464 kHz	175.937 kHz	100kHz≤&≤300kHz
40℃	8.1	175.466 kHz	175.932 kHz	100kHz≤&≤300kHz
	9.0	175.468 kHz	175.936 kHz	100kHz≤&≤300kHz
OFR		0.473kHz		
Results		PASS		



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

Test Mode: Mode 4

Frequency Range Test Result

Test Temperature	Test Voltage (V DC)	Lowest Frequency (fL)	Highest Frequency (fH)	Limit
-10℃	8.1	115.634 kHz	175.968 kHz	100kHz≤&≤300kHz
	9.0	115.634 kHz	175.966 kHz	100kHz≤&≤300kHz
25℃	9.0	115.633 kHz	175.969 kHz	100kHz≤&≤300kHz
40℃	8.1	115.635 kHz	175.968 kHz	100kHz≤&≤300kHz
	9.0	115.633 kHz	175.967 kHz	100kHz≤&≤300kHz
OFR		60.336kHz		
Results		PASS		


NOTE: All the modes had been tested, but only the worst data recorded in the report.

5.3 TRANSMITTER OUT OF BAND (OOB) EMISSIONS

MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Jun. 12, 2019	Jun. 11, 2020
Amplifier	ETS-LINDGREN	3117PA	00225134	Oct. 15, 2019	Oct. 14, 2020
LOOP ANTENNA	LAPLACE	RF300	--	Feb. 19, 2019	Feb. 18, 2021

TEST SETUP:



TEST PROCEDURE:

- 1). The EUT was placed on a turn table which is 0.8m above ground plane.
- 2). The EUT was modulated by normal signal,
- 3). Set SPA Center Frequency = fundamental frequency, RBW=VBW=200Hz, Span=5KHz, Detector=RMS. The 99 % OBW function shall be used to determine the operating frequency range, fH is the frequency of the upper marker resulting from the OFR, fL is the frequency of the lower marker resulting from the OFR.
- 4). Both normal test condition and extreme test condition applied

LIMITS

The OOB limits are visualized in figures; they are descending from the intentional limits from Table 3 at f_H/f_L with 10 dB/decade.




Figure 4: Out of band and spurious domain of a single frequency WPT system

TEST RESULT

Test Mode: Mode 3

Frequency range (KHz)		Maximum level @10m (dBuA/m)	Limit @ 10m (dBuA/m)	Result
$f_{SL} - f_L$	174.365 to 175.433	Less than -20.09	See figure 4	Pass
f_L	175.433	-20.09	-5.00	Pass
f_H	175.967	-20.61	-5.00	Pass
$f_H - f_{SH}$	175.967 to 177.035	Less than -20.61	See figure 4	Pass

Test Mode: Mode 1

frequency range (KHz)		Maximum level @10m (dBuA/m)	Limit @ 10m (dBuA/m)	Result
$f_{SL} - f_L$	174.518 to 175.464	Less than -19.24	See figure 4	Pass
f_L	175.464	-19.24	-5.00	Pass
f_H	175.937	-19.76	-5.00	Pass
$f_H - f_{SH}$	175.937 to 176.883	Less than -19.76	See figure 4	Pass



Test Mode: Mode 4

Frequency range (KHz)		Maximum level @10m (dBuA/m)	Limit @ 10m (dBuA/m)	Result
fSL -fL	114.565 to 115.633	Less than -19.07	See figure 4	Pass
fL	115.633	-19.07	42.00	Pass
fH	175.969	-22.39	-5.00	Pass
fH - fSH	175.969 to 177.045	Less than -22.39	See figure 4	Pass

NOTE: All the modes had been tested, but only the worst data recorded in the report.



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118


5.4 TRANSMITTER SPURIOUS EMISSIONS

MEASUREMENT EQUIPMENT USED:


NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Jun. 12, 2019	Jun. 11, 2020
Amplifier	ETS-LINDGREN	3117PA	00225134	Oct. 15, 2019	Oct. 14, 2020
LOOP ANTENNA	LAPLACE	RF300	--	Feb. 19, 2019	Feb. 18, 2021
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 09, 2019	Jan. 08, 2021

TEST SETUP:

FREQUENCY RANGE (9KHZ-30MHZ)




FREQUENCY RANGE (ABOVE 30MHZ)



SUBSTITUTION METHOD:

RADIATED BELOW 1GHZ



TEST PROCEDURE:

For test method of frequency range (9 kHz-30MHz)

The EUT was placed on the top of an insulating table 0.8 meters above the ground at a semi-anechoic chamber.

The table was rotated 360 degrees to determine the position of the highest radiation.

The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

The H-field is measured with a shielded loop antenna connected to a measurement receiver.

The measuring bandwidth and detector type of the measurement receiver shall be in accordance with EN 300 330 Table 1.

For test method of frequency range (30 MHz-1000MHz)

EUT was placed on a 1.5m height wooden table. The search antenna is placed at 3m distances from the EUT and search antenna height is from 1-4m. With the transmitter operating at continuously mode, the turntable was slowly rotated to locate the direction of maximum emission. Once maximum direction is determined, the search antenna was raised and lowered in both vertical and horizontal polarizations.

The EUT was removed from the turntable and replaced with a linearly polarized antenna connected to a calibrated RF signal generator. The RF generator was set to a measured emission frequency and the search antenna was raised and lowered to produce a maximum received reading. The generator output was increased to match the radiated emission reading measured previously, and the result expressed in dB EIRP or ERP, correcting for substitution antenna gain at each frequency.

LIMITS OF RADIATED DISTURBANCES

Below 30MHz

Table 4

State (see note)	Frequency $9 \text{ kHz} \leq f < 10 \text{ MHz}$	Frequency $10 \text{ MHz} \leq f < 30 \text{ MHz}$
Operating	27 dB μ A/m at 9 kHz descending 10 dB/dec	-3,5 dB μ A/m
Standby	5,5 dB μ A/m at 9 kHz descending 10 dB/dec	-25 dB μ A/m
NOTE: "Operating" means mode 2, 3 and 4 according to Table 2; "standby" means mode 1 according to Table 2.		

Table 5

State (see note)	47 MHz to 74 MHz 87,5 MHz to 118 MHz 174 MHz to 230 MHz 470 MHz to 790 MHz	Other frequencies between 30 MHz to 1 000 MHz
Operating	4 nW	250 nW
Standby	2 nW	2 nW
NOTE: "Operating" means mode 2, 3 and 4 according to Table 2; "standby" means mode 1 according to Table 2.		



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

TEST LIMITS & RESULT

Test Mode: Mode 3
FREQUENCY RANGE (9KHZ-30MHZ)

Operation Mode					
Frequency	Reading level	Total Factor	Emission level	Limit	Margin
(MHz)	(dB μ A)	(dB/m)	(dB μ A/m)	(dB μ A/m)	(dB μ A/m)
0.055	-7.64	-7.96	-15.60	19.15	34.74
0.311	-11.25	-7.96	-19.21	11.62	30.82
0.811	-12.74	-7.96	-20.70	7.45	28.15
1.617	-14.37	-3.98	-18.35	4.45	22.80
2.492	-12.99	-3.09	-16.08	2.58	18.66
3.005	-12.47	-1.25	-13.72	1.76	15.49

Remark:

- (1) Corrected Power (dBm) = Total Factor + Reading Level
- (2) Measuring frequencies from 9KHz to the 30MHz.
- (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

FREQUENCY RANGE (ABOVE 30MHZ)

Transmitter Spurious Emission below 1GHz (30MHz-1GHz)

Frequency	Reading Level	Antenna	S.G.	Cable Loss	Ant.Gain	Emission Level	Limit	Margin
(MHz)	(dBuv/m)	Polarization	(dBm)	(dB)	(dBi)	(dBm)	(dBm)	(dB)
84.87	30.50	V	-62.12	0.48	0.54	-62.06	-36.00	26.06
129.65	30.54	V	-61.32	0.49	0.14	-61.67	-36.00	25.67
239.98	31.49	V	-65.41	0.52	6.60	-59.33	-36.00	23.33
326.21	30.45	V	-67.68	0.53	6.10	-62.11	-36.00	26.11
334.47	31.81	V	-66.37	0.53	5.94	-60.96	-36.00	24.96
827.48	31.45	V	-66.29	0.66	6.45	-60.49	-54.00	6.49
83.75	32.51	H	-57.16	0.48	0.38	-57.26	-36.00	21.26
131.27	30.21	H	-58.88	0.49	0.08	-59.29	-36.00	23.29
243.18	30.00	H	-65.57	0.52	6.78	-59.31	-36.00	23.31
325.81	30.73	H	-65.94	0.53	6.10	-60.37	-36.00	24.37
735.70	31.07	H	-65.61	0.59	6.60	-59.60	-54.00	5.60
827.91	30.92	H	-65.18	0.66	6.45	-59.39	-54.00	5.39

Note: 1.The margins of the other spectrum are not exceeding the minimum value of margin, and this part of the results without recording in the test report.

2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "--" remark, if no specific emission from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.

Test Mode: Mode 4(The low channel is the worst case)
FREQUENCY RANGE (9KHZ-30MHZ)

Operation Mode					
Frequency	Reading level	Total Factor	Emission level	Limit	Margin
(MHz)	(dB μ A)	(dB/m)	(dB μ A/m)	(dB μ A/m)	(dB μ A/m)
0.033	-8.07	-7.96	-16.03	21.34	37.37
0.256	-11.21	-7.96	-19.17	12.47	31.63
0.677	-12.83	-7.96	-20.79	8.24	29.02
1.695	-14.68	-3.98	-18.66	4.25	22.91
2.371	-13.12	-3.09	-16.21	2.79	19.00
4.112	-12.47	-1.25	-13.72	0.40	14.12

Remark:

(1) Corrected Power (dBm) = Total Factor + Reading Level

(2) Measuring frequencies from 9KHz to the 30MHz.

(3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



FREQUENCY RANGE (ABOVE 30MHZ)

Transmitter Spurious Emission below 1GHz (30MHz-1GHz)

Frequency	Reading Level	Antenna	S.G.	Cable Loss	Ant.Gain	Emission Level	Limit	Margin
(MHz)	(dBuv/m)	Polarization	(dBm)	(dB)	(dBi)	(dBm)	(dBm)	(dB)
85.13	30.87	V	-59.01	0.48	0.70	-58.79	-36.00	22.79
130.03	30.82	V	-61.42	0.49	0.10	-61.81	-36.00	25.81
240.21	30.77	V	-64.63	0.52	6.60	-58.55	-36.00	22.55
326.22	30.02	V	-67.58	0.53	6.10	-62.01	-36.00	26.01
335.07	31.84	V	-63.21	0.53	5.90	-57.84	-36.00	21.84
827.96	31.77	V	-65.81	0.66	6.45	-60.02	-54.00	6.02
83.41	32.27	H	-58.65	0.48	0.38	-58.75	-36.00	22.75
131.72	30.29	H	-60.30	0.49	0.08	-60.71	-36.00	24.71
242.70	30.49	H	-67.66	0.52	6.72	-61.46	-36.00	25.46
325.64	30.99	H	-64.97	0.53	6.10	-59.40	-36.00	23.40
735.11	30.94	H	-66.32	0.59	6.60	-60.31	-54.00	6.31
827.32	31.16	H	-64.53	0.66	6.45	-58.74	-54.00	4.74

Note: 1. The margins of the other spectrum are not exceeding the minimum value of margin, and this part of the results without recording in the test report.

2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "--" remark, if no specific emission from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.

Test Mode: Mode 1
FREQUENCY RANGE (9KHZ-30MHZ)

Standby Mode					
Frequency	Reading level	Total Factor	Emission level	Limit	Margin
(MHz)	(dB μ A)	(dB/m)	(dB μ A/m)	(dB μ A/m)	(dB μ A/m)
0.067	-7.63	-7.96	-15.59	-3.22	12.37
0.245	-10.10	-7.96	-18.06	-8.85	9.21
0.560	-11.53	-7.96	-19.49	-12.44	7.05
1.689	-23.31	-3.98	-27.29	-17.23	10.06
2.661	-28.10	-3.09	-31.19	-19.21	11.98
4.363	-26.77	-1.25	-28.02	-21.36	6.66

Remark:

- (1) Corrected Power (dBm) = Total Factor + Reading Level
- (2) Measuring frequencies from 9KHz to the 30MHz.
- (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

FREQUENCY RANGE (ABOVE 30MHZ)

Transmitter Spurious Emission below 1GHz (30MHz-1GHz)

Frequency	Reading Level	Antenna	S.G.	Cable Loss	Ant.Gain	Emission Level	Limit	Margin
(MHz)	(dBuv/m)	Polarization	(dBm)	(dB)	(dBi)	(dBm)	(dBm)	(dB)
86.32	30.65	V	-71.83	0.48	0.84	-71.47	-57.00	14.47
238.34	31.79	V	-76.99	0.52	6.60	-70.91	-57.00	13.91
313.75	29.68	V	-77.17	0.53	6.31	-71.39	-57.00	14.39
383.74	30.00	V	-76.66	0.54	6.47	-70.73	-57.00	13.73
664.41	30.42	V	-77.24	0.59	6.98	-70.85	-57.00	13.85
879.42	30.91	V	-76.46	0.69	5.87	-71.28	-57.00	14.28
83.92	32.07	H	-71.27	0.48	0.38	-71.37	-57.00	14.37
110.52	30.70	H	-72.27	0.48	1.40	-71.35	-57.00	14.35
219.11	30.67	H	-77.77	0.52	7.38	-70.91	-57.00	13.91
485.58	30.52	H	-77.58	0.56	7.00	-71.14	-57.00	14.14
554.60	30.42	H	-79.71	0.57	6.78	-73.50	-57.00	16.50
635.51	30.87	H	-78.62	0.58	7.20	-72.00	-57.00	15.00

Note: 1.The margins of the other spectrum are not exceeding the minimum value of margin, and this part of the results without recording in the test report.


2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "--" remark, if no specific emission from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.

5.5 RECEIVER BLOCKING

MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	S/N	Cal. Date	Cal. Due
MXG X-Series Vector Signal Generator	Agilent	N5182B	MY50140530	Sep. 09, 2019	Sep. 08, 2020
LOOP ANTENNA	LAPLACE	RF300	N/A	Feb. 19, 2019	Feb. 18, 2021
Clamp meter	PROVA	PROVA-11	17200101	Sep. 09, 2019	Sep. 08, 2020

TEST SETUP:



TEST PROCEDURE:

- 1). The test shall be carried out inside a test chamber according to clauses C.1.1 and C.1.2 in ETSI EN 300 330
- 2). A test loop with a radius r shall be used to create the magnetic field; the test loop shall lie on a non-metallic ground and the minimum distance to metallic objects (e.g. ground plane) shall be 0,75 m. The EUT shall be placed to the centre of the test-loop
- 3). The test loop shall be sufficiently large so that the test loop itself does not influence the WPT system; The radius R of the test-loop shall be in minimum $\Delta R = 0,75$ m larger than the maximum dimension r of the EUT.

$$R \geq r + \Delta R.$$

The maximum H-Field can be calculated from the loop current I (into the test-loop) with the following formula:

$$H = I/2R$$

4) The required output current to achieve the required magnetic field at the WPT system shall be generated with a signal generator (unmodulated signal) at the test frequencies. For each test frequency the "reaction" of the device shall be recorded and checked against the performance criterion

LIMITS

The EUT shall achieve the wanted performance criterion, in the presence of the blocking signal.

Table 6: Receiver blocking limits

	In-band signal	OOB signal	Remote-band signal
Frequency	Centre frequency (f_c) of the WPT system (see clause 4.3.3)	$f = f_c \pm F$ (see note)	$f = f_c \pm 10 \times F$ (see note)
Signal level field strength at the EUT	72 dB μ A/m	72 dB μ A/m	82 dB μ A/m
NOTE: F = OFR see clause 4.3.3.			

TEST RESULT

Test Mode: Mode 3

Test Frequency(KHz)		Signal level @ EUT	Performance	Result
In-band signal	175.700	72dBuA/m	No function loss	Pass
OOB signal	175.166	72dBuA/m	No function loss	Pass
	176.234	72dBuA/m	No function loss	Pass
Remote-band signal	170.360	82dBuA/m	No function loss	Pass
	181.040	82dBuA/m	No function loss	Pass

Test Mode: Mode 1

Test Frequency(KHz)		Signal level @ EUT	Performance	Result
In-band signal	175.700	72dBuA/m	No function loss	Pass
OOB signal	175.227	72dBuA/m	No function loss	Pass
	176.173	72dBuA/m	No function loss	Pass
Remote-band signal	170.970	82dBuA/m	No function loss	Pass
	180.430	82dBuA/m	No function loss	Pass



6. INTERPRETATION OF MEASUREMENT RESULTS


All the measurement equipments and accessories have been carefully selected to meet the maximum measurement uncertainty specified below:

RF Frequency	$\pm 1 \times 10^{-7}$
RF Power, Conducted	$\pm 0.75\text{dB}$
Maximum Frequency Deviation: _ Within 300Hz and 6KHz of Audio Frequency _ Within 6KHz and 25KHz of Audio Frequency	$\pm 5\%$ $\pm 3\text{dB}$
Adjacent channel power	$\pm 3\text{dB}$
Conducted Emission of Transmitter, Valid Up to 12.75GHz	$\pm 4\text{dB}$
Conducted Emissions of Receivers	$\pm 3\text{dB}$
Radiated Emission of Transmitter, Valid Up to 12.75GHz	$\pm 6\text{dB}$

P.S. Uncertainty figures are valid to confidence level of 95% calculated according to the methods described in the ETSI TR 100 028.



APPENDIX A: PHOTOGRAPHS OF TEST SETUP



APPENDIX B: PHOTOGRAPHS OF THE EUT

Refer to the Report No.: AGC04094190911AP01

----END OF REPORT----



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118