

Health Test Report

Report No.: AGC04094190905EH02

PRODUCT DESIGNATION : Swiss Peak Luxury 5W wireless charging tray
BRAND NAME : N/A
MODEL NAME : P308.07
APPLICANT : Xindao B.V.
DATE OF ISSUE : Nov. 28, 2019
STANDARD(S) : EN 62311:2008
REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Nov. 28, 2019	Valid	Initial Release



TABLE OF CONTENTS

1. TEST REPORT CERTIFICATION.....	4
2. GENERAL INFORMATION.....	5
2.1. DESCRIPTION OF EUT	5
3. TEST SETUP	6
2.1 STANDARD APPLICABLE	6
2.2 EVALUATION METHODS.....	7
2.3 EVALUATION EQUIPMENT	8
2.4 EVALUATION RESULTS	8



1. TEST REPORT CERTIFICATION

Applicant	Xindao B.V.
Address	P.O. Box 3082, 2280 GB, Rijswijk, The Netherlands
Manufacturer	Xindao B.V.
Address	P.O. Box 3082, 2280 GB, Rijswijk, The Netherlands
Factory	Xindao B.V.
Address	P.O. Box 3082, 2280 GB, Rijswijk, The Netherlands
Product Designation	Swiss Peak Luxury 5W wireless charging tray
Brand Name	N/A
Test Model	P308.07
Date of test	Sep. 09, 2019 to Nov. 28, 2019
Deviation	None
Condition of Test Sample	Normal
Test Result	Pass
Report Template	AGCRT-EC-RF

We, Attestation of Global Compliance (Shenzhen) Co., Ltd. for compliance with the requirements set forth in the European Standard EN 62311. The results of testing in this report apply to the product/system which was tested only.

Prepared By



Donjon Huang
(Project Engineer)

Nov. 28, 2019

Reviewed By



Max Zhang
(Reviewer)

Nov. 28, 2019

Approved By



Forrest Lei
(Authorized Officer)

Nov. 28, 2019

2. GENERAL INFORMATION

2.1. DESCRIPTION OF EUT

The EUT is a short range, WPT device.

Details of technical specification refer to the description in follows:

Hardware Version	LWK-W-FC-002&001-5W
Software Version	V1.0
Operate Frequency	Energy transmission:110-205kHz Data communication:173.4KHz
Antenna Type	Integral antenna
Power Supply	DC 5V 2A

NOTE: 1. For more information, please refer to User's Manual.



3. TEST SETUP

2.1 STANDARD APPLICABLE

According to EN 62311:2008, Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz – 300 GHz).

Reference levels for electric, magnetic and electromagnetic fields
(0 Hz to 300 GHz, unperturbed rms values)


Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (μT)	Equivalent plane wave power density S_{eq} (W/m ²)
0-1 Hz	—	$3,2 \times 10^4$	4×10^4	—
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	—
8-25 Hz	10 000	$4\,000/f$	$5\,000/f$	—
0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	—
0,8-3 kHz	$250/f$	5	6,25	—
3-150 kHz	87	5	6,25	—
0,15-1 MHz	87	$0,73/f$	$0,92/f$	—
1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	—
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375\ f^{1/2}$	$0,0037\ f^{1/2}$	$0,0046\ f^{1/2}$	$f/200$
2-300 GHz	61	0,16	0,20	10



2.2 EVALUATION METHODS

Measurement of E and H field

A commonly used probe size is 100 cm², also the contribution of the three axes X, Y and Z can be evaluated separately.



Note: Position A: Front of EUT; Position B: Left of EUT; Position C: back of EUT; Position D: Right of EUT; Position E: Top of EUT

Based on the above standard limit, any device with output power below 5A/m cannot produce an exposure exceeding this restriction under the most pessimistic exposure conditions.

2.3 EVALUATION EQUIPMENT

Description	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Broadband Field Meter	Narda Safety Test Solutions GmbH	NBM-550	J-0004	Jun.12, 2019	Jun.11, 2020
Probe FHP	Narda Safety Test Solutions GmbH	EHP-50F	J-0015	Jun.12, 2019	Jun.11, 2020

2.4 EVALUATION RESULTS

Frequency	Maximum Radiated H-Field at 5cm		Limit	Result
MHz	A/m		A/m	Pass/Fail
110-205kHz	position E	0.046	4.2	Pass
	position A	0.013		
	position B	0.013		
	position C	0.013		
	position D	0.013		

Since Radiated H-Field at worse case is 0.046A/m, which cannot exceed the exempt condition, 4.2A/m. It is deemed to full fit the requirement of RF exposure basic restriction specified in EC Council Recommendation (1999/519/EC).

