

## HEALTH TEST REPORT

Prepared for :  
Address :

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,  
Bao'an District, Shenzhen, Guangdong, China  
Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : November 21, 2018  
Number of tested samples : 1  
Serial number : Prototype  
Date of Test : November 21, 2018 ~ November 30, 2018  
Date of Report : December 03, 2018



## HEALTH TEST REPORT

EN 62479: 2010

Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz).

Report Reference No. .... : LCS181121010AEC

Date of Issue ..... : December 03, 2018

Testing Laboratory Name ..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address ..... : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,  
Bao'an District, Shenzhen, Guangdong, ChinaTesting Location/ Procedure ..... : Full application of Harmonised standards ☒  
Partial application of Harmonised standards ☐  
Other standard testing method ☐

Applicant's Name..... :

Address ..... :

## Test Specification

Standard ..... : EN 62479: 2010

Test Report Form No. .... : LCSEMC-1.0

TRF Originator ..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF ..... : Dated 2011-03

## Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description. .... : Fabric Bluetooth Speaker

Trade Mark ..... : N/A

Test Model ..... :

Ratings ..... : Power Supply: 3.7V by battery (1200mAh)

Recharge Voltage: 5V $\overline{\text{---}}$ , 585mA Max

Result ..... : Positive

Compiled by:

Camille Li

Camille Li / Administrators

Supervised by:

Calvin Weng

Calvin Weng/ Technique principal

Approved by:



Gavin Liang/ Manager

## HEALTH -- TEST REPORT

**Test Report No. : LCS181121010AEC**December 03, 2018  
Date of issue

Test Model..... : XO-9567-1

EUT..... : Fabric Bluetooth Speaker

**Applicant**..... :

Address..... :

Telephone..... :

Fax..... :

**Manufacturer**..... :

Address..... :

Telephone..... :

Fax..... :

**Factory**..... :

Address..... :

Telephone..... :

Fax..... :

**Test Result****Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Revision History

Revision	Issue Date	Revisions	Revised By
000	December 03, 2018	Initial Issue	Gavin Liang

## 1. GENERAL INFORMATION

### 1.1. Product Description for Equipment Under Test (EUT)

EUT	: Fabric Bluetooth Speaker
Test Model	: XO-9567-1
Power Supply	: Power Supply:3.7V by battery (1200mAh) Recharge Voltage: 5V $\overline{\text{---}}$ , 585mA Max
Hardware Version	: V4.2
Software Version	: V1.1
Bluetooth	:
Frequency Range	: 2.402-2.480GHz
Channel Number	: 79 channels for Bluetooth V2.1 (BDR/EDR)
Channel Spacing	: 1MHz for Bluetooth V2.1 (BDR/EDR)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V2.1 (BDR/EDR)
Bluetooth Version	: V2.1
Antenna Description	: PCB Antenna, -0.58dBi

### 1.2. Objective

According to its specifications, the EUT must comply with the requirements of the following standards:  
EN 62479: 2010 –Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)

### 1.3. Test Methodology

All measurements contained in this report were conducted with EN 62479: 2010.

### 1.4. Description of Test Facility

FCC Registration Number. is 254912.  
Industry Canada Registration Number. is 9642A-1.  
ESMD Registration Number. is ARCB0108.  
UL Registration Number. is 100571-492.  
TUV SUD Registration Number. is SCN1081.  
TUV RH Registration Number. is UA 50296516-001  
NVLAP Registration Code is 600167-0

### 1.5. Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
DELL	PC	Vostro 15-7570	--	CE
DELL	Power adapter	ADP-90DDB	--	CE

## 1.6. External I/O

I/O Port Description	Quantity	Cable
AUX Port	1	N/A
USB Port	1	N/A

## 1.7. Equipment

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

## 1.8. Measurement Uncertainty

Parameter	Uncertainty
Occupied Channel Bandwidth	5 %
RF output power, conducted	1,5 dB
Power Spectral Density, conducted	3 dB
Unwanted Emissions, conducted	3 dB
All emissions, radiated	6 dB
Temperature	1 °C
Humidity	5 %
DC and low frequency voltages	3 %
Time	5 %
Duty Cycle	5 %

## 2. HUMAN EXPOSURE TO THE ELECTROMAGNETIC FIELDS

### 2.1 Test Methodology

#### 2.1.1.General description of applied standards

According to its specifications, the EUT must comply with the requirements of the following standards:  
EN 62479- Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)

#### 2.1.2.Description of test modes

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

### 2.2 Test limit

If the average power emitted by apparatus operating in the frequency range 10 MHz – 300GHz is less than or equal to 20 mW and the transmitting peak power is less than 20 W then the apparatus is deemed to comply with the basic restrictions without testing.

### 2.3 Test Results

Since Max. output power for Bluetooth is 1.663mW (2.21dBm According to radio test report LCS181121010AEB ) less than 20mW specified in EN 62479. This unit will not generate the harmful EM emission above the reference level as specified in EC Council Recommendation (1999/519/EC).

The unit complies with the EN 62479 for RF exposure requirement.

No non-compliance noted.

-----THE END OF REPORT-----