



Microtest  
微 测 检 测

# Test Report

Report No.: MTi19122404-3E3

Date of issue: May 09, 2020

Sample Description: Rolled-up Mouse Pad Wireless Charger

Model(s):

Applicant:

Address:

Date of Test: Jan. 03, 2020 - May 09, 2020

Shenzhen Microtest Co., Ltd.  
<http://www.mtitest.com>



This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen Microtest Co., Ltd.

Tel: (86-755) 88850135

Fax: (86-755) 88850136

Web: <http://www.mtitest.com>

E-mail: [mti@51mti.com](mailto:mti@51mti.com)

Address: No.102A & 302A, East Block, Hengfang Industrial Park, Xingye Road, Xixiang, Bao'an District, Shenzhen, Guangdong, China

THIS DOCUMENT WAS REDACTED WITH THE PRODUCTIP REDACTION TOOL ON 2020-07-01. AT THE TIME OF GENERATING THE DOCUMENT THE ORIGINAL DOCUMENT WAS AVAILABLE ALSO. THE ORIGINAL CAN ONLY BE MADE AVAILABLE BY THE DOCUMENT OWNER.



## Table of Contents

1	General description .....	4
1.1	Feature of equipment under test (EUT) .....	4
1.2	Testing site .....	4
2	EN 62311 requirement.....	5
2.1	General information .....	5
2.2	Limits .....	5
2.3	Result .....	6



TEST RESULT CERTIFICATION	
Applicant's name:	
Address:	
Manufacture's name:	
Address:	
Product name:	Rolled-up Mouse Pad Wireless Charger
Trademark:	
Model name:	
Standards:	EN 62311: 2008

This device described above has been tested by Shenzhen Microtest Co., Ltd. and the test results show that the equipment under test (EUT) is in compliance with the Radio equipment directive requirements. And it is applicable only to the tested sample identified in the report.

Tested by:

Danny Xu

May 09, 2020

Reviewed by:

Leo Su

May 09, 2020

Approved by:

Tom Xue

May 09, 2020



## 1 General description

### 1.1 Feature of equipment under test (EUT)

Product name:	Rolled-up Mouse Pad Wireless Charger
Model name:	
Serial Model:	N/A
Deference in serial model:	N/A
Power source:	DC 9V from adapter AC 230V/50Hz
Adapter information:	N/A

### 1.2 Testing site

Test laboratory:	Shenzhen Microtest Co., Ltd.
Laboratory location:	No.102A & 302A, East Block, Hengfang Industrial Park, Xingye Road, Xixiang, Bao'an District, Shenzhen, Guangdong, China
CNAS Registration No.:	L5868
Telephone:	(86-755)88850135
Fax:	(86-755)88850136



## 2 EN 62311 requirement

### 2.1 General information

The essential requirements of Directive 99/5/ec in the article 3.1(a) and the limits must be taken from Council Recommendation 99/519/EC for General Population or from the ICNIRP Guidelines for Occupational Exposure, EN 62311:2008 Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz – 300 GHz).

### 2.2 Limits

Reference levels for electric, magnetic and electromagnetic fields (0Hz to 300GHz)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field ( $\mu$ T)	Equivalent plane wave power density $S_{eq}$ (W/m <sup>2</sup> )
0-1Hz	-	$3.2 \times 10^4$	$4 \times 10^4$	-
1-8Hz	10000	$3.2 \times 10^4 / f^2$	$4 \times 10^4 / f^2$	-
8-25Hz	10000	$4000 / f$	$5000 / f$	-
0.025-0.8kHz	$250 / f$	$4 / f$	$5 / f$	-
0.8-3kHz	$250 / f$	5	6.25	-
3-150kHz	87	5	6.25	-
0.15-1MHz	87	$0.73 / f$	$0.92 / f$	-
1-10MHz	$87 / f^{1/2}$	$0.73 / f$	$0.92 / f$	-
10-400MHz	28	0.073	0.092	2
400-2000MHz	$1.375 f^{1/2}$	$0.037 f^{1/2}$	$0.0046 f^{1/2}$	$f / 200$
2-300GHz	61	0.16	0.2	10

Note:

(1) As indicated in the frequency range column.

(2) For frequencies between 100 kHz and 10GHz, Seq, E2, H2 and B2 are to be averaged over any six-minute period.

(3) For frequencies exceeding 10GHz, Seq, E2, H2 and B2 are to be averaged over any 68/.1.05-minute period (.in GHz).

(4) No E-field value is provided for frequencies <1Hz, which are effectively static electric fields. For most people the annoying perception of surface electric charges will not occur at field strengths less than 20kV/m. Spark discharges causing stress or annoyance should be avoided.



## 2.3 Result

Frequency (KHz)	d(cm)	Max E-field strength (V/m)	Limit E-field strength (V/m)	Result
110-205	20	0.77	87	Pass

----END OF REPORT----