Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Suppl	lier'	s n	ame	or tı	ade m	ark: DI	GITUS					

Supplier's address:	Product Management,	Auf dem Schüffel 3,	58513 Lüdenscheid, DE

Model identifier:	DN-19 LIGHT-3
-------------------	---------------

Type	of light	source:
------	----------	---------

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	NA		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter		Value	Parameter	Value			
General product parameters:							
	mption in on- 100 h), rounded est integer	3	Energy efficiency class	F			
indicating if it r in a sphere (3	us flux (φuse), refers to the flux 60º), in a wide in a narrow cone	300 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500			
On-mode pressed in W	oower (P _{on}),	3,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
for CLS, expre	ndby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82			
Outer	Height	300	Spectral power	See image			
dimensions	Width	28	distribution in the	in last page			
				Dago 1 / 2			

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	9	range 250 nm to 800 nm, at full-load				
Claim of equiva	lent power ^(a)	-	If yes, equivalent power (W)	-			
			Chromaticity	0,315			
			coordinates (x and y)	0,338			
Parameters for LED and OLED light sources:							
R9 colour rende	ering index value	3	Survival factor	1,00			
the lumen main	tenance factor	0,95					

(a)'-': not applicable;

(b)'-': not applicable;

